



1SS417FN2

Surface Mount Schottky Barrier

Voltage

40 V

Current

100 mA

Features

- Small package
- Low forward voltage : $V_{F(3)}=0.51V(\text{Typ.})$
- Low reverse current : $I_R=5\mu A(\text{Max.})$
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard

Mechanical Data

- Case : DFN1006-2L Package
- Terminals : Solderable per MIL-STD-750, Method 2026
- Approx. Weight : 0.0006 grams

DFN1006-2L



Maximum Ratings and Thermal Characteristics (T_A = 25°C unless otherwise noted)

PARAMETER	SYMBOL	LIMIT	UNITS
Maximum (Peak) Reverse Voltage	V _{RM}	45	V
Peak Reverse Voltage	V _R	40	V
Maximum (Peak) Forward Current	I _{FM}	200	mA
Average Forward Current	I _O	100	mA
Surge Current (10ms)	I _{FSM}	1	A
Power Dissipation	P _D	100	mW
Operating Junction Temperature Range	T _J	-55~125	°C
Storage Temperature Range	T _{STG}	-55~125	°C



1SS417FN2

Electrical Characteristics (T_A = 25°C unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNITS
Forward Voltage	V _{F1}	I _F = 1 mA	-	0.26	-	V
	V _{F2}	I _F = 10 mA	-	0.34	-	
	V _{F3}	I _F = 100 mA	-	0.51	0.62	
Reverse Current	I _R	V _R = 40 V	-	-	5	μA
Junction Capacitance	C _J	V _R = 0 V, f = 1 MHz	-	10	-	pF



1SS417FN2

TYPICAL CHARACTERISTIC CURVES




Fig.1 Forward Current Derating Curve




Fig.2 Typical Junction Capacitance




Fig.3 Typical Reverse Characteristics




Fig.4 Typical Forward Characteristics





1SS417FN2

Product and Packing Information

Part No.	Package Type	Packing Type	Marking	Version
1SS417FN2	DFN1006-2L	10K pcs / 7" Reel	7F	Halogen free RoHS compliant

Packaging Information & Mounting Pad Layout





1SS417FN2

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.