



NOTES:

MATERIAL

- ⑤ 1. Insulator Material: PA9T+30%GF(UL94V-0), Black
 - 2. Contact Material : Brass
 - 3. Contact Plating : Gold flash Over 50µ"Ni
- ELECTRICAL**
- 1. Current Rating : 1.5AMP
 - 2. Withstand Voltage : 500V AC/DC
 - 3. Contact Resistance : 20mΩ max
 - 4. Insulation Resistance: 1000MΩ min
- ENVIRONMENTAL**
- 1. Operation Temperature: -40°C to +105°C
 - ④ 2. Packing: Tube

Order Information :

xx: 06,08,10,14,16,20,24,26,30,34,40,44,50,60

RoHS compliant

 File No.: E198287 ③

| Scale | Free | | | | | | | |
|-----------|-------|---|-----------------------------|------------|--------|--------------|------------|--------|
| TOLERANCE | | ⑤ | Change the material to PA9T | 22.03.2016 | Winnie | Drawn | 25.01.2006 | Alex |
| X.X | ±0.40 | ④ | Update the packing | 24.02.2014 | Amy | Approved | 22.03.2016 | Winnie |
| X.XX | ±0.25 | ③ | Add UL-File No | 12.12.2013 | Winnie | | | |
| X.XXX | ±0.15 | ② | Update | 29.06.2009 | Dean | | | |
| Angle° | ±3° | ① | Drawn | 25.01.2006 | Alex | | | |
| | | | Id. | | | Modification | | |



| | |
|-----------------|----------------|
| Customer-No. | |
| ASSMANN WSW-No. | AWHW2 XXG-0202 |
| Drawing-No. | ASS 2317 CO |
| Replace | rev05 |
| Sheet | |

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | A |
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | A |
| H | G | F | E | D | C | B | A |