



SIGN	DATE	DESCRIPTION	APPROVER
△			

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- Item A Terminal housing: Thermoplastic (UL94V-0)
- Item B Terminal cover: Thermoplastic (UL94V-0)
- Item C Female contact : Copper. Tin plated
- Item D Wire guard : Stainless Steel
- Item E Clamp : Steel Stamping , Zinc plated
- Item F Handle: Steel t=1.5mm, Zinc plated
- Item G Terminal screw: Zinc plating"-slot type,M5
- Item H With flange screw: Zinc plating"x-slot type,M5

Electrical:

- Voltage rating: 600 V
- Current rating: 115 A
- Wire range:
- Solid wire(AWG): 2-20
- Stranded wire(AWG): 2-20
- Torque(Lb-In): 36.5
- Screw: M5
- Wire strip length: 19-20mm
- Withstanding Voltage: 2.2 KV
- Operating temperature: -40°C to +115°C
- APPROVAL:

KX 04 C 1 x 2 xxxx G

No. OF POLES _____ G: Pb<4000ppm
 04: 4 POLES _____ 0000: "@ " Logo (Standard)
 COLOR _____ 000A: "ANYTEK" Mark
 Any special item by customer request.
 please contact sales department.

0: BLACK
 5: GREEN (RAL 6018/T)
 6: BLUE
 8: GREY (RAL 7035/D)

ANYTEK				CUSTOMER COPY				
								ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD
TITLE		KX 15.0mm Series (with handle) 4P						
PART NO.		KX04C1x2xxxxG			DWG NO.		8KX0002	
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance	
			Runner 2011.04.25	Runner 2010.05.24			X. ±0.50 X.X ±0.30 X.XX ±0.10 X° ±1°	
				SHEET: 01/01		REV.: B		