2-2205129-2 - ACTIVE

TE Internal #: 2-2205129-2 INDUSTRIAL MINI I/O Pigtail Cable Assembly, 8 Positions, 3.28 ft [1 m], 1 Gb/s, Black Cable, Shielded, 26 AWG, .129 mm², Twisted Pair View on TE.com >



Cable Assemblies > Copper Cable Assemblies > Pluggable I/O Cable Assemblies



Cable Assembly Type: INDUSTRIAL MINI I/O Pigtail

Equalized: No

Wire Size: .129 mm²

Outside Cable Diameter: 6.2 mm [.244 in]

Features

Product Type Features

Latching Style	Slide Latch
Cable Assembly Category	Industry Standard
Cable Assembly Type	INDUSTRIAL MINI I/O Pigtail
Connector Type (End A)	INDUSTRIAL MINI I/O Plug

Cable Style	Twisted Pair	
Configuration Features		
Number of Positions	8	
Number of Signal Positions	8	
Electrical Characteristics		
Impedance	100 Ω	
Signal Characteristics		
Data Rate	1 Gb/s	
Body Features		
Shield Material	Copper Alloy	
Jacket Material	PUR	
Equalized	No	
Cable Color	Black	
Cable Flammability Rating	UL 444	
Contact Features		

2-2205129-2

INDUSTRIAL MINI I/O Pigtail Cable Assembly, 8 Positions, 3.28 ft [1 m], 1 Gb/s, Black Cable, Shielded, 26 AWG, .129 mm², Twisted Pair



Contact Mating Area Plating Material Thickness19.68 μm[.5 μin]Contact Mating Area Plating MaterialGoldHousing FeaturesThermoplasticHousing MaterialThermoplasticDimensions.129 mm²Outside Cable Diameter6.2 mm[.244 in]
Housing Features Housing Material Thermoplastic Dimensions Wire Size .129 mm²
Housing MaterialThermoplasticDimensions.129 mm²
Dimensions Wire Size .129 mm ²
Wire Size .129 mm ²
Outside Cable Diameter 6.2 mm[244 in]
Operation/Application
Shielded Yes
Halogen Free Yes
Industry Standards
Performance Category Cat 5e
Other
Cable Assembly Configuration Single Ended
Cable Assembly Length 1 m[3.28 ft]

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous

2-2205129-2

INDUSTRIAL MINI I/O Pigtail Cable Assembly, 8 Positions, 3.28 ft [1 m], 1 Gb/s, Black Cable, Shielded, 26 AWG, .129 mm², Twisted Pair



materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought



ETE	Contraction of the second seco	C TE	371
TE Part #34111	TE Part #2-1393222-0	TE Part #130446	TE Part #2-2205130-3
SOLIS R 22-16 COMM 22-18 MIL 8	V23061A1005A302=MINISTARKSTROM	PIDG RING	CA MINI IO TYPE II PIGTAIL



Documents

Product Drawings CA MINI IO TYPE I PIGTAIL

2-2205129-2

INDUSTRIAL MINI I/O Pigtail Cable Assembly, 8 Positions, 3.28 ft [1 m], 1 Gb/s, Black Cable, Shielded, 26 AWG, .129 mm², Twisted Pair



English

Product Specifications Application Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English