

HC-STA-B48-SHWS-2SSP36-EMC-AL - Housing



1424866

<https://www.phoenixcontact.com/us/products/1424866>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Box mounting bases B48, with single locking latch, material: Die-cast aluminum, salt water resistant, cable outlets: 2, lateral, 2x Pg36, height: 99 mm, cable gland: none, Standard

Your advantages

- Good shielding in the event of electromagnetic interference

Commercial data

Item number	1424866
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF56
Product key	BF7APB
Catalog page	Page 645 (C-2-2019)
GTIN	4055626382715
Weight per piece (including packing)	1,030.5 g
Weight per piece (excluding packing)	880 g
Customs tariff number	85389099
Country of origin	CN

1424866


<https://www.phoenixcontact.com/us/products/1424866>

Technical data

Product properties

Type	B48
Product type	Housing with locking latch
Application	Standard
No. of cable outlets	2
Type of the screw connection	2x Pg36
Housing type	Box mounting bases
Cable outlet	lateral
Pg screw connection	none

Dimensions

Dimensional drawing	
Width	120 mm
Height	99 mm
Length	132 mm
Hole diameter	6.5 mm

Material specifications

Flammability rating according to UL 94	V0 (Interlock)
Seal material	NBR, conductive
Housing surface material	uncoated
Locking latch material	PA
Impact strength	IK08
Housing material	Die-cast aluminum, salt water resistant

Mechanical properties

Mechanical data

Type of the screw connection	2x Pg36
Locking type	Latch

Mounting

Assembly instructions	One opening is sealed with a plastic filler plug and can be opened using a screwdriver.
-----------------------	---

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66
----------------------	------

HC-STA-B48-SHWS-2SSP36-EMC-AL - Housing



1424866

<https://www.phoenixcontact.com/us/products/1424866>


	IP67
Degree of protection (NEMA)	4 (UL 50e)
	4X (UL 50e)
	12 (UL 50e)
Impact strength	IK08
Ambient temperature (operation)	-40 °C ... 125 °C

1424866

<https://www.phoenixcontact.com/us/products/1424866>

Drawings

Dimensional drawing



Dimensional drawing

1424866

<https://www.phoenixcontact.com/us/products/1424866>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1424866>

DNV

Approval ID: TAE000037S

ENEC

EAC

Approval ID: RU C-DE.BL08.B.00511

1424866

<https://www.phoenixcontact.com/us/products/1424866>

Classifications

ECLASS

ECLASS-11.0	27440202
ECLASS-12.0	27440202
ECLASS-13.0	27440202

ETIM

ETIM 8.0	EC000437
----------	----------

UNSPSC

UNSPSC 21.0	31261500
-------------	----------

HC-STA-B48-SHWS-2SSP36-EMC-AL - Housing



1424866

<https://www.phoenixcontact.com/us/products/1424866>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

HC-STA-B48-SHWS-2SSP36-EMC-AL - Housing



1424866

<https://www.phoenixcontact.com/us/products/1424866>

Accessories

US-EMLP (20X9) CUS - Plastic label

0830085

<https://www.phoenixcontact.com/us/products/0830085>

Plastic label, can be ordered: by card, white, labeled according to customer specifications, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 75



WP-G HF IP66 PG36 BK - Screw connection

3240894

<https://www.phoenixcontact.com/us/products/3240894>

Cable gland, Pg thread, IP66 protection, straight



HC-STA-B48-SHWS-2SSP36-EMC-AL - Housing

1424866

<https://www.phoenixcontact.com/us/products/1424866>

WP-G HF IP69K PG36 BK - Screw connection

3240880

<https://www.phoenixcontact.com/us/products/3240880>



Cable gland, Pg thread, IP68/69k protection, straight

WP-G PP HF PG21 - Screw connection

3240992

<https://www.phoenixcontact.com/us/products/3240992>



Cable gland made from PP with Pg thread, IP65 protection

HC-STA-B48-SHWS-2SSP36-EMC-AL - Housing

1424866

<https://www.phoenixcontact.com/us/products/1424866>



WP-GA HF IP69K PG36 BK - Screw connection

3240908

<https://www.phoenixcontact.com/us/products/3240908>

Cable gland, Pg thread, IP68/69k protection, angled



WP-GR HF IP66 PG36 BK - Screw connection

3240950

<https://www.phoenixcontact.com/us/products/3240950>

Cable gland, Pg thread, IP66 protection, with strain relief



HC-STA-B48-SHWS-2SSP36-EMC-AL - Housing

1424866

<https://www.phoenixcontact.com/us/products/1424866>

WP-GR HF IP69K PG36 BK - Screw connection

3240936

<https://www.phoenixcontact.com/us/products/3240936>



Cable gland, Pg thread, IP68/69k protection, with strain relief

WP-G PP HF PG36 - Screw connection

3240994

<https://www.phoenixcontact.com/us/products/3240994>



Cable gland made from PP with Pg thread, IP65 protection

HC-STA-B48-SHWS-2SSP36-EMC-AL - Housing

1424866

<https://www.phoenixcontact.com/us/products/1424866>

WP-GT PP HF PG36 - Screw connection

3241008

<https://www.phoenixcontact.com/us/products/3241008>



Cable gland made from PP with Pg thread, rotatable, IP54 protection

WP-G BRASS IP40 PG36 - Screw connection

3241043

<https://www.phoenixcontact.com/us/products/3241043>



Cable gland made from brass with Pg thread, IP40 protection

HC-STA-B48-SHWS-2SSP36-EMC-AL - Housing



1424866

<https://www.phoenixcontact.com/us/products/1424866>

WP-GT BRASS PG36 - Screw connection

3241029

<https://www.phoenixcontact.com/us/products/3241029>

Cable gland made from brass with Pg thread, rotatable, IP40 protection



WP-G BRASS IP65 PG36 - Screw connection

3241057

<https://www.phoenixcontact.com/us/products/3241057>

Cable gland made from brass with Pg thread, IP65 protection



Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com