


## HC-WRV-PG29

Order No.: 1666838

The illustration shows version HC- WRV-PG 21

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1666838>

Corrugated tube screw connection, for corrugated tube, to lead individual conductors and wires with IP65 protection into the housings of the industrial connectors HEAVYCON, type Pg29

Commercial data	
GTIN (EAN)	 4 017918 136918
sales group	D096
Pack	10 pcs.
Customs tariff	39174000
Catalog page information	Page 557 (PC-2009)

**Product notes**WEEE/RoHS-compliant since:  
10/31/2006

<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
<b>General data</b>	
Cable gland material	PA
Inflammability class acc. to UL 94	HB
Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 110 °C

## Certificates / Approvals



Certification

GOST

---

## Diagrams/Drawings

Dimensioned drawing

### **Assembly instructions for Pg29 corrugated pipe**

a = Corrugated screw connection

b = Corrugated pipe

c = Opener

#### *Installation note:*

Cut the corrugated pipe in the groove to retain a round shape for insertion. The lighter seal (not depicted in the illustration) is positioned in the corrugated pipe screw connection below the safety latch. The darker outer seal (not depicted in the illustration) is placed over the corrugated pipe screw connection from outside. The corrugated pipe is then pushed as far as possible into the corrugated pipe screw connection and clicks into place. The screw connection is opened by placing the yellow corrugated pipe opener with force between the safety latch and the corrugated tube and the corrugated pipe is then pulled out.

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2010 Phoenix Contact  
Technical modifications reserved;