XZCPA0566L5

Pre wired connectors XZ, straight female, M8, 3 pins, cable PUR 5 m



Main	
Range of Product	Telemecanique Cabling components
Accessory / separate part category	Cabling accessory
Accessory / Separate Part Type	Pre-wired connectors
Series name	Application

Complementary

Complementary		
Electrical connection	Straight female connector M8, 3 pins	
Cable connector fixing	Screw-on	
Collar material	Stainless steel 316L	
Status LED	Without	
Cable length	16.40 ft (5 m)	
Cable outer diameter	0.20 in (5 mm)	
Cable composition	3 x 0.34 mm²	
Wire insulation material	PUR	
[Ue] rated operational voltage	75 V DC	
Line Rated Current	4 A	
Contact resistance	5000 μOhm	
Minimum insulating resistance	1 GΩ	
Net Weight	0.39 lb(US) (0.175 kg)	

Environment

IP Degree of Protection	IP68
Ambient air temperature for operation	-13185 °F (-2585 °C) static
Ambient Air Temperature for Storage	-31212 °F (-35100 °C)

Ordering and shipping details

Category	22483-MACHINE CABLES
Discount Schedule	DS3
GTIN	3389119021579
Nbr. of units in pkg.	1
Package weight(Lbs)	6.56 oz (186.0 g)
Returnability	No
Country of origin	PL

Packing Units


PCE	
0.98 in (2.5 cm)	
5.71 in (14.5 cm)	
5.71 in (14.5 cm)	
S03	
	0.98 in (2.5 cm) 5.71 in (14.5 cm) 5.71 in (14.5 cm)

Number of Units in Package 2	40	
Package 2 Weight	17.36 lb(US) (7.873 kg)	
Package 2 Height	11.81 in (30 cm)	
Package 2 width	11.81 in (30 cm)	
Package 2 Length	15.75 in (40 cm)	
Offer Sustainability		
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	[®] REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₽ Yes	

Contractual warranty

Warranty	1	8 months


Dimensions



L: Lenght of cable

Connections and Schemes

Connector



BU : Blue BN : Brown BK : Black