### SPECIFICATION CONTROL DRAWING

**CHEMINAX** 

75 OHM, AWG 22, 19 STRANDS OF AWG 34, TWINAXIAL CABLE

Date 12-7-12
Revision A

7522B0331

THIS SPECIFICATION SHEET FORMS A PART OF THE LATEST ISSUE OF RAYCHEM SPECIFICATION 1200.

# **CONSTRUCTION DETAILS**

## **ELECTRICAL CHARACTERISTICS**

DIMENSIONS ARE NOMINAL VALUES IN INCHES UNLESS OTHERWISE DESIGNATED.

**CONDUCTORS** AWG 22, 19 Strands of .0315 AWG 34, Tin-Coated Copper **DIELECTRICS** .060 Rayolin F ±.003 Colors - Tan/White **DRAINWIRE** AWG 22, 19 Strands of AWG 34, Tin-Coated Copper **WRAP** .128 Aluminum Polyester

Outer jacket color will be black (designated by a "-0" appended to the part number, e.g. 7522B0331-0) unless otherwise specified.

JACKET

Thermorad S

Designate outer jacket color with a dash number in accordance with MIL-STD-681. Other codes and suffixes may be added to the part number, as necessary, to capture any additional requirements imposed by the purchase order.

CHARACTERISTIC IMPEDANCE 75 ± 7 ohms, Method C at 1 MHz
MUTUAL CAPACITANCE 30.0 pF/ft. (nominal)

VELOCITY OF PROPAGATION 66% (nominal)

## ADDITIONAL REQUIREMENTS

#### **ELECTRICAL**

CONDUCTOR RESISTANCE 15.5 ohms/1000 ft. (nominal)

(prior to cabling)

INSULATION RESISTANCE 10,000 megohms (minimum)

for 1000 ft.

JACKET FLAWS

SPARK TEST 1.0 kV (rms)
IMPULSE TEST 6.0 kV (peak)

VOLTAGE WITHSTAND (DIELECTRIC) 1000 volts (rms) (minimum)

#### **ENVIRONMENTAL**

FLAMMABILITY Method C HEAT SHOCK 225°C

LOW TEMPERATURE-COLD BEND -55°C/4.25 inch mandrel

VOLTAGE WITHSTAND 1000 volts (rms), 1 minute

(Post Environmental)

#### **PHYSICAL**

INSULATION (DIELECTRIC)

(Prior to Cabling)

ELONGATION 200% (minimum)
TENSILE STRENGTH 1800 lbf/in² (minimum)

**JACKET** 

ELONGATION 200% (minimum)
TENSILE STRENGTH 2000 lbf/in² (minimum)

JACKET THICKNESS .013 inch (nominal)

WRAP .002 inch thick (nominal)

25% minimum overlap Aluminum side facing out

WEIGHT 14.4 lbs/1000 ft. (nominal)

Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics Corporation also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.

Page 1 of 1

.154

Rayolin, Thermorad, Cheminax, Raychem, TE Connectivity, TE connectivity (logo) and TE (logo) are trademarks.

