

## Han PushPull Power 4/0-F metall crimp



Image is for illustration purposes only. Please refer to product description.

Part number	09 35 231 0401
Specification	Han PushPull Power 4/0-F metall crimp
HARTING eCatalogue	<a href="https://b2b.harting.com/09352310401">https://b2b.harting.com/09352310401</a>

### Identification

Category	Connectors
Series	Han® PushPull (V14)
Identification	Power
Element	Connector sets
Features	Intuitive locking mechanism

### Version

Termination method	Crimp termination
Shielding	Unshielded
Number of contacts	5
Locking type	PushPull
Pack contents	incl. metal housing and female insert Without contacts

### Technical characteristics

Conductor cross-section	0.25 ... 2.5 mm <sup>2</sup>
Conductor cross-section	AWG 22 ... AWG 12
Rated current	16 A
Rated voltage conductor-earth	400 V
Rated voltage conductor-conductor	690 V
Rated impulse voltage	6 kV
Pollution degree	2
Rated voltage acc. to UL	600 V



Pushing Performance  
Since 1945

## Technical characteristics

Limiting temperature	-40 ... +70 °C
Mating cycles	≥500
Degree of protection acc. to IEC 60529	IP65 IP67
Clamping range	4 ... 11 mm
Vibration resistance	5-150 Hz, 5 g, 0.35 mm, 2h/axis
Shock resistance	5 g / 30 ms, 3 shocks / axis and direction

## Material properties

Material (insert)	Thermoplastic
Surface (contacts)	Silver plated
Material (hood/housing)	Zinc die-cast
Surface (hood/housing)	Nickel plated
Material (O-ring)	NBR
Material (cable seal)	TPE
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	6,6'-di-tert-butyl-2,2'-methylenedi-p-cresol Lead
ECHA SCIP number	be45dcda-0f90-459a-a8bc-78fb7986a295
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel

## Specifications and approvals

Specifications	IEC 61076-3-118
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076

## Specifications and approvals

Approvals	DNV GL
-----------	--------

## Commercial data

Packaging size	1
Net weight	66.2 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140054196
eCl@ss	27440114 Rectangular connector (for field assembly)

## Mating face

