



## Item description

### Features:

- Switched-mode power supply
- Stepped profile for installation in standard distribution boards
- Screw mounts for alternative installation in distribution boxes or devices
- Pluggable *picoMAX®* Connection Technology (tool-free)

—  
Subject to changes. Please also observe the further product documentation!

- Suitable for both parallel and series operation
- Electrically isolated output voltage (SELV) per EN 60335-1 and UL 60950-1; PELV per EN 60204

## Data

### Technical data

#### Input

|  |   |
|--|---|
| Phases                                   | 1   |
| Nominal input voltage $U_{i\text{ nom}}$ | 1 x AC 100 ... 120 V; AC 200 ... 240 V                  |
| Input voltage range                      | 1 x AC 90 ... 132 V; AC 180 ... 264 V; DC 250 ... 375 V |
| Input voltage derating                   | -2 %/V (< 100 VAC)                                      |
| Nominal mains frequency range            | 47 ... 63 Hz; 0 Hz                                      |
| Input current $I_i$                      | $\leq 3.8 \text{ A}$                                    |
| Inrush current                           | $\leq 20 \text{ A}$                                     |
| Power factor                             | $\geq 0.5$  |
| Power factor correction (PFC)            | Passive   |
| Mains failure hold-up time               | $\geq 30 \text{ ms}$                                    |

#### Output

|  |  |
|--|--|
| Nominal output voltage $U_{o\text{ nom}}$  | DC 24 V (SELV)   |
| Output voltage range                       | DC 22 ... 27 V (adjustable)  |
| Default setting                            | DC 24 V  |
| Nominal output current $I_{o\text{ nom}}$  | 6 A; 4.8 A (< 110 VAC)   |
| Nominal output power                       | 150 W  |
| Deviation                                  | $\leq 1 \%$  |
| Deviation, dynamic load change 10 ... 90 % | $\leq 1 \%$  |
| Residual ripple                            | $\leq 100 \text{ mV}$ (peak-to-peak)   |
| Overload behavior                          | Constant power (in overload range: $1.05 \dots 1.35 \times I_{o\text{ nom}}$ ); Shutdown and automatic restart in the event of a short circuit or permanent overload |

#### Signaling and Communication

|                            |                       |
|----------------------------|-----------------------|
| Signaling                  | 1 x LED DC OK (green) |
| Operation status indicator | Green LED ( $U_o$ )   |

Subject to changes. Please also observe the further product documentation!

## Efficiency/power losses

|  |                                |
|--|--------------------------------|
| Power loss P <sub>I</sub>              | ≤ 0.4 W                        |
| Power loss (max.) P <sub>I(max.)</sub> | 16.5 W (100 VAC / 24 VDC; 6 A) |
| Efficiency (typ.)                      | 90 % (230 VAC); 89 % (110 VAC) |

## Circuit protection

|                             |  |
|-----------------------------|--|
| Internal fuse               | T 3.15 A / 500 VAC   |
| Backup fusing (required)    | An external DC fuse is required for the DC input voltage.                  |
| Backup fusing (recommended) | Circuit breaker: 6 A (C characteristic), 10 A (B characteristic) or higher |

## Safety and protection

|                                   |                                    |
|-----------------------------------|------------------------------------|
| Protection class                  | I                                  |
| Protection type                   | IP20; per EN 60529                 |
| Pollution degree                  | 2                                  |
| Transient suppression (primary)   | Varistor                           |
| Overvoltage protection; secondary | ≤ 31 VDC (in the event of a fault) |
| Short-circuit-protected           | Yes                                |
| Open-circuit-proof                | Yes                                |
| Parallel operation                | Yes                                |
| Series operation                  | Yes                                |
| MTBF                              | > 500,000 h (per IEC 61709)        |

## Connection data

|                         |                                    |
|-------------------------|------------------------------------|
| Connection type 1       | Input/Output                       |
| Connection technology   | Push-in CAGE CLAMP®                |
| WAGO connector          | picoMAX® 5.0, WAGO 2092 Series     |
| Solid conductor         | 0.2 ... 2.5 mm² / 24 ... 12 AWG    |
| Fine-stranded conductor | 0.2 ... 2.5 mm² / 24 ... 12 AWG    |
| Strip length            | 9 ... 10 mm / 0.35 ... 0.39 inches |

## Physical data

|        |                       |
|--------|-----------------------|
| Width  | 144 mm / 5.669 inches |
| Height | 90 mm / 3.543 inches  |
| Depth  | 56 mm / 2.205 inches  |

Subject to changes. Please also observe the further product documentation!

|                                   |                              |
|-----------------------------------|------------------------------|
| Depth from upper-edge of DIN-rail | 52.5 mm / 2.067 inches       |
| Note (dimensions)                 | Depth: 48 mm (without cover) |

## Mechanical Data

|                |                                   |
|----------------|-----------------------------------|
| Housing design | DIN-rail-mount enclosure          |
| Mounting type  | DIN-35 rail<br>Screw mount (back) |

## Material Data

|                             |          |
|-----------------------------|----------|
| Flammability class per UL94 | V0       |
| Fire load                   | 0.243 MJ |
| Weight                      | 510 g    |

## Environmental requirements

|                                 |   |
|---------------------------------|---|
| Ambient temperature (operation) | -25 ... +70 °C                                  |
| Ambient temperature (storage)   | -40 ... +85 °C                                  |
| Relative humidity               | 95% (no condensation permissible)               |
| Derating                        | -2.66 %/K (> 55 °C)                             |
| Climatic category               | 3K3 (per EN 60721; except for low air pressure) |

## Standards and specifications

|                          |  |
|--------------------------|--|
| Conformity marking       | CE   |
| Standards/specifications | EN 61204-3<br>EN 60335-1<br>EN 62368-1<br>UL 60950-1<br>UL 508 |

## Commercial data

|                   |             |
|-------------------|-------------|
| eCl@ss 10.0       | 27-04-07-01 |
| eCl@ss 9.0        | 27-04-07-01 |
| ETIM 8.0          | EC002540    |
| ETIM 7.0          | EC002540    |
| Recupel Type      |             |
| PU (SPU)          | 1 pcs       |
| Packaging type    | box         |
| Country of origin | CN          |

Subject to changes. Please also observe the further product documentation!

|                       |               |
|-----------------------|---------------|
| GTIN                  | 4055143415040 |
| Customs tariff number | 85044083900   |

## Environmental Product Compliance

|   |                                      |
|---|--------------------------------------|
| RoHS Compliance Status                    | Compliant, No Exemption              |
| SCIP notification number (Bulgaria)       | 705848bc-74cb-41b0-a444-3c4311c395fd |
| SCIP notification number (Czech Republic) | bfa67b36-0252-4066-be38-f1d0cf4f723b |

## Approvals / Certificates

### General approvals

| Logo | Approval                                      | Additional Approval Text       | Certificate name                        |
|------|---|--------------------------------|---|
|      | <b>EAC</b><br>Brjansker Zertifizierungsstelle | TP TC 004/2011, TP TC 020/2011 | EAC RU C-<br>DE.AM02.<br>B.<br>00089_19 |
|      | <b>UL</b><br>Underwriters Laboratories Inc.   | UL 60950-1                     | E255815                                 |
|      | <b>UL</b><br>Underwriters Laboratories Inc.   | UL 508                         | E255817                                 |

### Declarations of conformity and manufacturer's declarations

| Logo | Approval  | Additional Approval Text | Certificate name |
|------|---|--------------------------|------------------|
|      | <b>EU-Declaration of Conformity</b><br>WAGO GmbH & Co. KG | -                        | -                |

## Optional accessories

### Strain relief

|                     |  |  |
|---------------------|--|--|
| Strain relief plate | <b>Item no.: 2092-1601</b><br>Gripping plate; for female and male connectors; 1 part; Pin spacing 5 mm; 3- to 4-pole; light gray | <a href="http://www.wago.com/2092-1601">www.wago.com/2092-1601</a> |
|---------------------|--|--|

### Tool

|                |   |  |
|----------------|---|--|
| Operating tool | <b>Item no.: 210-719</b><br>Operating tool; Blade: 2.5 x 0.4 mm; with a partially insulated shaft | <a href="http://www.wago.com/210-719">www.wago.com/210-719</a> |
|                | <b>Item no.: 210-769</b><br>SCREWDRIVER; green  | <a href="http://www.wago.com/210-769">www.wago.com/210-769</a> |

Subject to changes. Please also observe the further product documentation!

## Downloads

### Documentation

#### Manual

|  |                        |               |          |
|--|------------------------|---------------|----------|
| Product Manual COMPACT Power; 1-phase<br>DC 24 V / 6 A | V 1.0.1<br>2021 年1月21日 | pdf<br>1.7 MB | Download |
|--|------------------------|---------------|----------|

#### Bid Text

|                          |               |                 |          |
|--------------------------|---------------|-----------------|----------|
| 787-1226<br>X81 - Datei  | 2019 年11月25 日 | xml<br>7.3 kB   | Download |
| 787-1226<br>docx - Datei | 2019 年11月25 日 | docx<br>18.4 kB | Download |
| ausschreiben.de 787-1226 |               | URL             | Download |

#### Instruction Leaflet

|  |  |               |          |
|--|--|---------------|----------|
| Primär getaktete Stromversorgungen COMPACT<br>DC 24 V, 6 A |  | pdf<br>1.6 MB | Download |
|--|--|---------------|----------|

#### Additional Information

|   |                         |               |          |
|---|-------------------------|---------------|----------|
| Disposal and Recycling<br>Electrical and electronic equipment, Batteries, Packaging | V 1.1.0<br>2022 年8月18 日 | pdf<br>2.2 MB | Download |
|---|-------------------------|---------------|----------|

## CAD/CAE-Data

### CAE data

|                            |  |     |          |
|----------------------------|--|-----|----------|
| EPLAN Data Portal 787-1226 |  | URL | Download |
| ZUKEN Portal 787-1226      |  | URL | Download |
| WSCAD Universe 787-1226    |  | URL | Download |

### CAD data

|                       |  |     |          |
|-----------------------|--|-----|----------|
| 2D/3D Models 787-1226 |  | URL | Download |
|-----------------------|--|-----|----------|

Subject to changes. Please also observe the further product documentation!

## Environmental Product Compliance

### Compliance Search

Environmental Product Compliance 787-1226

URL

Download

Switched-mode power supply; Compact; 1-phase; 24 VDC output voltage; 6 A output current; DC-OK LED

---

## Installation Notes

### Product family

[EPSITRON COMPACT Power](#)

[EPSITRON® COMPACT POWER: Compact, High-Performance Power Supplies](#)

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!

---

WAGO GmbH & Co. KG

Hansastraße 27

32423 Minden

Phone: +49 571 887-0 | Fax: +49 571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.