



SIGN	DATE	DESCRIPTION	APPROVER
△			
△			

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- Item 1 Terminal housing : Thermoplastic (UL 94V-0)
- Item 2 Clamp : Steel stamping , Zinc plated
- Item 3 Wire guard solder pin : Copper, Tin plated
- Item 4 Terminal screw : Steel , Zinc plating" - "slot type

Electrical cULus IEC

- Voltage rating : 300V 1000V
- Current rating : 65A 76A
- Wire range : 16.00mm
- Solid wire (AWG) : 6-20
- Stranded wire (AWG) : 6-20
- Torque (LB-In.) : 19LB-In
- Screw : M4.5
- Wire strip length : 10-11mm
- Withstanding voltage : 2.2KV 6KV
- Operating temperature : -40°C+115°C
- Soldering temperature : 250°C+10°C/5 Sec
- Safety Approval : US

VP xx 85 x 8 xxxx G

- | | | | |
|----------------|-----------------------|--|--------------|
| 02 2 CONTACTS | 0: Black | 0000 Standard @ Logo | RoHS |
| 03 3 CONTACTS | 5: Green (RAL 6018/T) | 000A Standard ANY Logo | Pb<40,000ppm |
| ... | 6: Blue | Any special item by customer request, please contact sales department. | |
| 12 12 CONTACTS | 8: Grey (RAL 7035/D) | | |

Poles	02	03	04	05	06	07	08	09	10	11	12
Dim L	25.40	38.10	50.80	63.50	76.20	88.90	101.60	114.30	127.0	139.70	152.40
Dim B	12.70	25.40	38.10	50.80	63.50	76.20	88.90	101.60	114.30	127.0	139.70
TOL	±0.15			±0.20			±0.30				

ANYTEK				CUSTOMER COPY			
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD							
TITLE		VP 12.70 Series (0.9x1.0) Contacts Pin Pitch 4.0mm ----Double parallel tail					
PART NO.		VPxx85x8xxxxG			DWG NO.		8VP0120
APPROVED		CHECKED		DESIGNED		DRAWN	
		Aron 2009.11.16		Aron 2009.11.16		CUST NO.	
						Tolerance	
						X. ±0.50	
						X.X ±0.30	
						X.XX ±0.10	
						X° ±1°	
				SHEET: 01/01		REV.: B	