

RED INDICATES ORIGINAL

DASH NO	FIG NO	CABLE ACCOMMODATED	A DIM	B DIM	C HEX	D DIA	E FLATS	ASSEMBLE PER				
-003	1,2	RG-174, -188, -316	2.730	1.500	.178	.516	.437	TAI-117				
-004		RG-179, RG-187	2.450	1.220								
-008		RG-195, RG-180 421-111 ESSEX	2.730	1.500								
-009		8218 BELDEN YR23023 BELDEN 21-597 ESSEX	2.450	1.220								
-010		RG-122	2.730	1.500								
-011		RG-58, -141, -303 21-597 ESSEX	2.730	1.500								
-012		RG-55, -142, -223 RG-400	2.730	1.500								
-013		RG-59, RG-62	2.730	1.500								
-013A		TCC-75-2	2.450	1.220								
-014		8212 BELDEN	2.730	1.500								
-015		1	RG-71 730A AT&T	2.730					1.500	.290	.578	.500
-016		724 AT&T 8281 BELDEN	2.730	1.500								
-017		RG-6	2.730	1.500								
-018		1,2	9268 BELDEN	2.730					1.500	.255	.516	.437
-019	8279 BELDEN	2.730	1.500									
-020	1	9248 BELDEN	2.730	1.500	.290	.578	.500					
-023	1,2	89108 BELDEN	2.730	1.500	.255	.516	.437					
-025		734A AT&T	2.730	1.500								
-026		735A AT&T	2.730	1.500								
-027		KS19224L2 AT&T	2.730	1.500								
			2.450	1.220								
			2.450	1.220								

DVG SIZE C	DATA CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO TROMPETER ELECTRONICS INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED FOR PROCUREMENT OR MANUFACTURE WITHOUT EXPRESS WRITTEN PERMISSION.			REVISIONS		1-0453	SH IC
	REV	ED	DESCRIPTION	DWN	APPROVED	DATE	
V	1343B		ADDED -023 TO CABLES ACCOMMODATED AND -023/-W023 TO BDM; SEE ECO	DKC	[Signature]	5/24/60	




FIG 1 Δ
-003 SHOWN




FIG 2 Δ
-003 SHOWN

INCH	MM
.005	0.13
.030	0.76
.070	1.78
.090	2.29
.125	3.18
.178	4.52
.213	5.41
.255	6.48
.290	7.37
.312	7.92
.324	8.23
.340	8.65
.375	9.53
.437	11.10
.500	12.70
.516	13.11
.578	14.68
1.220	30.99
1.500	38.10
1.750	44.45
2.450	62.23
2.730	69.34

- Δ IF BEND RELIEF SPRING REQUIRED (FIG 2) ADD SUFFIX "BR" TO CABLE GROUP DASH NO (NOT AVAILABLE FOR CABLE GROUPS -015 THRU -W017, -020, -W020, -027 & -W027)
- 6. DASH NO DENDTES CABLE GROUP
- Δ SLEEVE REQUIRED ON -003 THRU -W004 ONLY
- Δ SLEEVE AND CRIMP SLEEVE ARE SUPPLIED LOOSE
- 3. COAXIAL STD .375 SIZE TDDL CRIMP PATCH PLUG BOTH RCA/AT&T VERSIONS (.070/.090 PIN CONTACT DIA)
- 2. FINISH: TFS-1A (NICKEL)
- 1. ALL DIM ARE IN INCHES

8. EXAMPLE OF COMPLETE MODEL NO:
 PL1WC-003 BR Δ
 BASIC MODEL NO
 PL1C = 50 DHM (.070)
 PL1WC = 75 DHM (.090) DASH NO



RECOMMENDED
 HEX CRIMP
 SCALE: NONE

11-03	QTY	DESCRIPTION	PART NUMBER	ITEM
11-02	TOL UNLESS SPECIFIED			
105-0998	.XX ±			
105-0972	.XXX ± .030			
1-0319	ANGLE ±			
1-0304	DWN DKC 5-12-00	MATERIAL	CODE IDENT	DRAWING NO.
1-0301	CHK [Signature]		14949	1-0453
	ENGR			REV V
	NEXT ASSY	SCALE 2/1	DATE 4-30-79	SHEET 1C