

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.



APPLICABLE STANDARD		STORAGE TEMPERATURE RANGE		-10°C T ₀ + 60°C (NOTE2)	
RATING	OPERATING TEMPERATURE RANGE	-45°C T ₀ +125°C (NOTES 1)		-10°C T ₀ + 60°C (NOTE2)	
	VOLTAGE	150V AC		DF9#-*S-1V(69)	
CURRENT	0.5A				
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS		QT	AT
CONSTRUCTION			ACCORDING TO DRAWING.		
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.				
MARKING	CONFIRMED VISUALLY.				
ELECTRIC CHARACTERISTICS					
CONTACT RESISTANCE	100m A(DC OR 1000 HZ).	50mΩ MAX.		X	-
INSULATION RESISTANCE	100V DC.	500MΩ MIN.		X	-
VOLTAGE PROOF	250V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.			
MECHANICAL CHARACTERISTICS					
MECHANICAL OPERATION	100TIMES INSERTIONS AND EXTRACTATIONS.	① CONTACT RESISTANCE: 50mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X	-
VIBRATION	FREQUENCY 10 TO 55 HZ, SINGLE AMPLITUDE 0.75 mm, AT 2 h, FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X	-
SHOCK	490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X	-
ENVIRONMENTAL CHARACTERISTICS					
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -65 → 5 TO 35 → 125 → 5 TO 35°C TIME 30→10 TO 15 → 30→10 TO 15min UNDER 5 CYCLES.	① CONTACT RESISTANCE: 50mΩ MAX. ② INSULATION RESISTANCE: 500 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X	-
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.	① CONTACT RESISTANCE: 50mΩ MAX. ② INSULATION RESISTANCE: 500 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.		X	-
CORROSION SALT MIST	EXPOSED IN 5% SALT WATER SPRAY FOR 48 h.	① CONTACT RESISTANCE: 50 mΩ MAX. ② NO HEAVY CORROSION.		X	-
SULPHUR DIOXIDE	EXPOSED IN 10 PPM FOR 96 h. (TEST STANDARD: JEIDA-39)	① CONTACT RESISTANCE: 50 mΩ MAX. ② NO HEAVY CORROSION.		X	-
HEAT RESISTANCE OF SOLDERING	[RECOMMENDED TEMPERATURE PROFILE] 《SOLDERING AREA》 MAX250°C, 220°C FOR 60 SECONDS MAX. 《PREHEATING AREA》 150 TO 180°C 90~120 SECONDS. MAXIMUM TWICE ACTION IS ALLOWED UNDER THE SAME CONDITION. [RECOMMENDED MANUAL SOLDERING CONDITION] SOLDERING IRON TEMPERATURE 380°C SOLDERING TIME : WITHIN 3 SECONDS.	NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.		X	-
SOLDERABILITY	SOLDERING TEMPERATURE: 245 ± 5°C DURATION OF IMMERSION : SOLDERING FOR 3SECONDS	A NEW UNIFORM COATING OF SOLDER SHALL COVER MINIMUM OF 95% OF THE SURFACE BEING IMMERSSED.		X	-
REMARKS					
NOTE1: INCLUDING THE TEMPERATURE RISE BY CURRENT. NOTE2: STORAGEIS DEFINED AS LONG-TERM STORAGE OF UNUSED PRODUCTS. APPLY OPERATION TEMPERATURE RANGE TO PRODUCTS MOUNTED ON PCB WITHOUT POWER SUPPLY. UNLESS OTHERWISE SPECIEHED , REFER TO JIS C 5402 .					
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	
1	DIS-H-001224	AR, TAKAHASHI	TS, MIYAZAKI	06.08.01	
		APPROVED	TY, OMA	04.04.06	
		CHECKED	TY, OMA	04.04.06	
		DESIGNED	HK, UMEHARA	04.04.02	
		DRAWN	MY, NAKAMOTO	04.04.02	
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.		ELC4-160018-13	
SPECIFICATION SHEET		PART NO.	DF9B-*P-1V(69)		
HIROSE ELECTRIC CO., LTD.		CODE NO.	CL540		
					1/1