



NOTES:

1. METALSHELLS: COPPER ALLOY; min. 315µin TIN over 40-80µin NICKEL
2. INSULATORS: PBT GF UL 94 V-0, BLACK (b)
3. SIGNAL CONTACTS: COPPER ALLOY  
PLATING: GOLD FLASH over NICKEL (b)  
SOLDER CUP ACCEPTS CABLE AWG 22
4. CONNECTOR IS PART MARKED: 4HDD44SAM99A10X CONEC ABC

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH  DO NOT ALTER CAD DRAWING BY HAND					tolerance	dim. in mm	scale:	2:1 (5:1)		
					date		name	material:	SEE NOTES	
					drawn	20.04.10	Henneboel	title: <b>D-SUB HD FEMALE</b> 44pos. SOLDER CUP for installation into water resistant hood		
					appd.	20.04.10	Fischer			
					norm					
					d-old			dwg no:	Inventor 10	DIN-A3
2 x b	A3897	03.01.11	K.H.				15K3A338		sh: 1	
a	Origin						part no:	4HDD44SAM99A10X		
rev.	description	date	name							