






APPROVED: _____
 DATE: _____ TITLE: _____

Rev	AWO #	Description	Date	Appr
-		RELEASED	1/26/21	





HEX NUT



LOCK WASHER

ANTI ROTATIONAL WASHER

INCLUDED HARDWARE



CIRCUIT DIAGRAM
(SPDT) MOMENTARY

SPECIFICATIONS:

Material:
 Movable Contact: Copper Alloy, Silver Plated
 Terminal: Copper Alloy, Silver Plated
 Electrical:
 Voltage rating: 120VAC or 38VDC
 Current rating: 1 Amps
 Contact resistance: 10 mΩ max
 Insulation resistance: 1,000 Mohms min
 Dielectric withstanding voltage: 1,500V RMS @Sea level
 Temperature Rating:
 Operating temperature: -30°C to +85°C
 Environmental:
 Lead free, RoHS compliant



UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE INCHES [MM] TOLERANCES: EXCEPT AS NOTED		 909 Rahway Avenue, Union, NJ 07083 Phone: 908-687-5000 Fax: 908-687-5710		
INCHES HOLES				
.X ± .10	∅.X ± .10	TITLE SNAP-ACTING PUSHBUTTON SWITCH, SPDT, ON-MOMENTARY, SILVER PLATED, SOLDER TYPE		
.XX ± .020	∅.XX ± .015			
.XXX ± .015	∅.XXX ± .010	SIZE X	PART NO. SW-PB8-AB00A1QE-1	REV. -
APPROVALS		REF: S00198T	SCALE: NTS	SHEET 1 OF 1
DRAWN	LH	DATE	1/26/21	
CHECKED	AC	DATE	1/26/21	
APPROVED				