


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00617	Connector, dc jack, 5.5x2.5x17.6mm, brass, nickel plated, molding type, threaded 5/16-32	1	
2	30-00007	Wire, 2C BC, 18 AWG, UL2468, 300V, 80C, 4.4 mm, VW-1, PVC	1	
3	24-00295	Overmold, dc jack, 5.5 mm, locking	1	PVC, black



Notes:
Functionally equivalent components may be substituted

Wiring Diagram	
50-00617	wire color
center	black with stripe
sleeve	black

Revision:	Date:	Description:	Prepared: AW <small>Digitally signed by AW Date: 2019.06.28 13:28:19 -07'00'</small>	Notes:	<h1>TENSILITY</h1> <p>tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com</p>
A	6/28/2019	Initial release	Verified: AG <small>Digitally signed by AG Date: 2019.06.28 14:27:13 -07'00'</small>	RoHS compliant	
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Function test: no open, no short circuit, no intermittent	
				Description: Cable, 2000 mm, 5.5x2.5 50-00617 locking dc jack to 5mm tinned, 18 AWG, UL2468, 30-00007 wire	
				Size:	Part number:
				A	10-03320
				Scale: 1:1	Sheet 1 of 1

5

4

3

2

1