

A.
System
Overview

B1.
Cable Ties

B2.
Cable
Accessories

B3.
Stainless
Steel Ties

C1.
Wiring
Duct

C2.
Surface
Raceway

C3.
Abrasion
Protection

C4.
Cable
Management

D1.
Terminals

D2.
Power
Connectors

D3.
Grounding
Connectors

E1.
Labeling
Systems

E2.
Labels

E3.
Pre-Printed
& Write-On
Markers

E4.
Permanent
Identification

E5.
Lockout/
Tagout
& Safety
Solutions

F.
Index

Tooling Selection Guide for *PANDUIT* Tubular Ring Terminals

Tooling	CT-1700	CT-720	CT-930, CT-930CH, CT-920, CT-920CH, CT-2920, CT-940CH	CT-980, CT-980CH, CT-2950, CT-2980	CT-2001
<i>PANDUIT</i> Part Number	<i>PANDUIT</i> Die Part Number Die Index Number (Number of Crimps)				
S8-10R-Q					
S8-14R-Q	P21	CD-720-1	CD-920-8	—	CD-2001-8
S8-56R-Q	(2)	P21 (1)	P21 (1)		P21 (1)
S8-38R-Q					
S6-10R-E					
S6-14R-E	P24	CD-720-1	CD-920-6	—	CD-2001-6
S6-56R-E	(2)	P24 (1)	P24 (1)		P24 (1)
S6-38R-E					
S4-10R-E					
S4-14R-E	P29	CD-720-1	CD-920-4	STD	CD-2001-4
S4-56R-E	(2)	P29 (1)	P28 (1)	(1)	P29 (1)
S4-38R-E					
S2-10R-X					
S2-14R-X	P37	CD-720-2	CD-920-1	STD	CD-2001-1
S2-56R-X	(3)	P37 (1)	P37 (1)	(1)	P37 (1)
S2-38R-X					
S2-12R-X					
S1/0-14R-X					
S1/0-56R-X	—	CD-720-2	CD-920-1/0	STD	CD-2001-1/0
S1/0-38R-X		P42 (1)	P42 (1)	(1)	P42 (1)
S1/0-12R-X					
S2/0-14R-X					
S2/0-56R-X	—	CD-720-2	CD-920-2/0	STD	CD-2001-2/0
S2/0-38R-X		P45 (2)	P45 (1)	(1)	P45 (2)
S2/0-76R-X					
S2/0-12R-X					
S3/0-14R-5					
S3/0-56R-5	—	CD-720-2	CD-920-3/0	STD	CD-2001-3/0
S3/0-38R-5		P50 (2)	P50 (1)	(1)	P50 (2)
S3/0-76R-5					
S3/0-12R-5					
S4/0-38R-5					
S4/0-76R-5	—	CD-720-3	CD-920-4/0	STD	CD-2001-4/0
S4/012R-5		P54 (2)	P54 (1)	(1)	P54 (2)
S250-56R-5					
S250-38R-5	—	CD-720-3	CD-920-250	STD	CD-2001-250
S250-76R-5		P62 (2)	P62 (1)	(1)	P62 (2)
S250-12R-5					

Tooling Selection Guide for PANDUIT Ferrules

PANDUIT Ferrule Series	Ferrule Description	Wire Range (AWG)	Wire Range (mm²)	Wire Strip Length	Controlled Cycle Hand Tools								
					CT-1000	CT-1002	CT-1003	CT-1004	CT-1005	CT-1006	CT-1104	CT-1123	
F	Non-insulated ferrules	24	.25	Please See Ferrule Tables – Pgs. D1.73 – D1.77		X	X						
		22 – 18	.50 – 1.00			X	X					X	
		16	1.50			X	X					X	
		14	2.50			X	X						
		12	4.00			X	X					X	
		10	6.00			X	X					X	
		8	10.0					X	X			X	
		6	16.0					X	X			X	
		4 – 2	25.0 – 35.0								X	X	
		1	50.0									X	
FSD, FSF	Insulated single wire ferrules (DIN or French color code)	26 – 18	.41 – 1.00		X	X						X	
		16 – 14	1.50 – 2.00		X	X						X	
		12 – 10	4.00 – 6.00		X	X						X	
		8	10.0				X	X			X	X	
		6	16.0				X	X			X		
		4 – 2	25.0 – 35.0						X				
1	50.0								X				
FTD	Insulated twin wire ferrules	22 – 18	.50 – 1.00		X	X						X	
		16 – 14	1.50 – 2.00		X	X						X	
		12	4.00				X	X				X	
		10	6.00				X	X			X		
FSD-DSL FS-DSL	Insulated single wire ferrules on strips of 50 (DIN or other color code)	20 – 14	.50 – 2.50	.31" (8mm)	X								

A.
System
Overview

B1.
Cable Ties

B2.
Cable
Accessories

B3.
Stainless
Steel Ties

C1.
Wiring
Duct

C2.
Surface
Raceway

C3.
Abrasion
Protection

C4.
Cable
Management

D1.
Terminals

D2.
Power
Connectors

D3.
Grounding
Connectors

E1.
Labeling
Systems

E2.
Labels

E3.
Pre-Printed
& Write-On
Markers

E4.
Permanent
Identification

E5.
Lockout/
Tagout
& Safety
Solutions

F.
Index