



PHANTOM® ANTENNAS - UHF TRA(B)(T)2100

PATENTED WHIPLESS PHANTOM® UHF ANTENNA'S FEATURE TRUE FIELD DIVERSITY DESIGN

Laird's unique patented Phantom® is a tough antenna for outdoor or indoor applications. Measuring only 3.5" tall, the Phantom® UHF antenna's revolutionary design features field diversity with both vertical and horizontal polarization components. This gives the antenna diversity, frequency agility, low visibility, wide bandwidth and a low angle radiation pattern that is superior to traditional gain antennas in most applications.

The industry standard NMO mounting socket mates with all Laird's magnetic, trunk lid, and hole mounts. A threaded permanent stud mount model is also available for vandal resistant mounting on brackets, panels, ceilings or any other kind of housing.

The Phantom® patented technology is beneficial when high performance is desired and extreme ruggedness and low profile is required.


FEATURES

- The antenna is available in both custom tune and field tunable options
- True field diversity design ensures uninterrupted transmissions in urban canyons and rural drop off areas
- Phantom out performs a 3 dB whip in many applications
- U.S. Patent Nos. 5,977,931 - 6,292,156 and 7,209,096

MARKETS

- Public safety
- Transportation
- Utility
- Military mobile
- Fixed radio applications

ANTENNA PATTERNS



Azimuthal Pattern (Y, Z, or E-plane)

ELECTRICAL SPECIFICATION	
Frequency Range	210-225 MHz
Frequency Bandwidth	2.2 MHz @VSWR < 2.0:1
VSWR	< 2.0:1
Return Loss	-10 dB min
Nominal Gain	Unity 3 dB-MEG (elevation = 0°) 5 dBi (elevation = 45°) -11 dBi (elevation = 90°)
Maximum Power	60W
Nominal Impedance	Ω50
Polarization	Vertically polarized
Pattern	Omnidirectional
Azimuthal Angle Coverage	360°
Lightning Protection	AC Ground
Cable	None
Termination	NMO
Tuning	Adhesive Tuning Disk

MECHANICAL SPECIFICATION

Size	Width = 3 - 1/4" Height = 3 - 1/2"
Weight	0.25 lbs
Finish	GE X-17 ABS
Color	White (Black also available)

MODEL AND ORDERING INFORMATION

MODEL	DESCRIPTION	TUNING OPTIONS
TRA2100	210-225 MHz VHF Phantom 3/4 NMO, White	Custom tune
TRAB2100	210-225 MHz VHF Phantom 3/4 NMO, Black	Custom tune
TRAT2100	210-225 MHz VHF Phantom 3/4 NMO, White	Field tunable
TRABT2100	210-225 MHz VHF Phantom 3/4 NMO, Black	Field tunable

Mounting Designed To:
4' x 4' metallic ground plane mobile applications

TE TECHNICAL SUPPORT CENTER

USA:	+1 (800) 522-6752
Canada:	+1 (905) 475-6222
Mexico:	+52 (0) 55-1106-0800
Latin/S. America:	+54 (0) 11-4733-2200
Germany:	+49 (0) 6251-133-1999
UK:	+44 (0) 800-267666
France:	+33 (0) 1-3420-8686
Netherlands:	+31 (0) 73-6246-999
China:	+86 (0) 400-820-6015

te.com

TE, and TE connectivity (logo) are trademarks owned or licensed by the TE Connectivity Ltd. family of companies. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

The information given herein, including drawings, illustrations and schematics which are intended for illustration purposes only, is believed to be reliable. However, TE Connectivity makes no warranties as to its accuracy or completeness and disclaims any liability in connection with its use. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect or consequential damages arising out of the sale, resale, use or misuse of the product. Users of TE Connectivity products should make their own evaluation to determine the suitability of each such product for the specific application.

TE Connectivity warrants to the original end user customer of its products that its products are free from defects in material and workmanship. Subject to conditions and limitations TE Connectivity will, at its option, either repair or replace any part of its products that prove defective because of improper workmanship or materials. This limited warranty is in force for the useful lifetime of the original end product into which the TE Connectivity product is installed. Useful lifetime of the original end product may vary but is not warranted to exceed one (1) year from the original date of the end product purchase.

©2022 TE Connectivity. All Rights Reserved.

08/22 Original