






RoHS Compliant

UC-263

LP uPCI 4xRS232 + LPT Printer Port

"SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



Features

- 4 port RS232
- PCI 3.0
- 64 Byte Tx and 64 Byte Rx FIFOs
- Up to 115,200 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

Options



UC-263: LP uPCI 4xRS232 + LPT Printer Port

Description

Universal PCI providing four RS232 serial ports and one LPT port 4 industry standard 9 pin D RS232 ports with 25 pin D LPT port on a flylead. Data transfer rates up to 115,200 baud rates and the 64 byte deep transmit and 64 byte receive FIFOS, coupled with 1Mbit/s line drivers deliver uncompromising performance on your PC.Includes drivers for all Windows 32 bit and 64 bit Operating Systems, including Windows 7.

With Brainboxes industry renowned Lifetime Warranty and Lifetime Support!

Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows 7 32 bit 64 bit Editions
- Windows Server 2008 32 bit 64 bit Editions
- Windows Vista 32 bit 64 bit editions
- Windows Server 2003 32 bit 64 bit Editions

As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.



ORDER Description LP uPCI 4xRS232 + LPT Printer Port

Code UC-263

+44(0) 151 220 2500 | sales@brainboxes.com | www.brainboxes.com

UC-263

LP uPCI 4xRS232 + LPT Printer Port

UC-263Full Specification

+44(0)

151 220 2500

4 x RS232 Ports Port Connector DB9 Connector 9 Pin Male and LPT port 25 Pin Female RS232 Pinout (9 Pin Male) Pin 1 DCD Pin 2 RXD Pin 1 Pin 5 FIFO size 64 RX FIFO + 64 TX FIFO Pin 3 TXD Pin 4 DTR EIA - RS232 Standard Pin 5 GND **Operating Distance** Pin 6 DSR Pin 7 RTS Cable No Cable; Integrated Connector Pin 8 CTS Pin 9 RI Baud Rate 115,200 Port Settings Data Bits 5,6,7 or 8 115,200 Parity Odd, Even, None, Mark or Space \rangle baud Stop Bits 1, 1.5 or 2 Flow Control Tx/Rx Modes Point to Point **OS** Compatibility Microsoft Windows 7 32 bit 64 bit Editions Interface Windows Server 2008 32 bit 64 bit Editions Windows Vista 32 bit 64 bit Editions Windows Server 2003 32 bit 64 bit Editions PCI Windows XP 32 bit 64 bit Editions DOS BUS Plus Printer Port : AEO C-TPAT Microsoft Certified Gold Partner WEEE RoHS EMC: CE TAA Industry Approvals Approvals Microsoft Approvals Windows 7 32 bit 64 bit Editions Windows Server 2008 32 bit 64 bit editions Windows Vista 32 bit 64 bit editions Windows Server 2003 32 bit 64 bit editions Windows XP 32 bit 64 bit editions PCB Layers 4 General Power Consumption 300mA @ 5V, 60mA @12V Weight 0.069 kg Size 135l x 18w x 80h mm Installation CD including manual, Microsoft signed drivers & utilities Packaging **Box Content** Card LP uPCI 4xRS232 + LPT Printer Port No Cable; Integrated Connector Lifetime (online registration required) Warranty **Product Support** Lifetime Web, Email and Phone Support from fully qualified, friendly Support staff who work in and alongside the Product Development Team **OEM** option Available for bulk buy OEM Additional Made In Manufactured in the UK by Brainboxes Winner 2005 European :lektra C Electronics Industry Awards "Manufacturer of the Year" WINNER Customisable Brainboxes operate a "Perfect Fit Custom Design" policy for volume Manufacturer of the Year Made in the UK users. More Info: sales@brainboxes.com

Other PCI Cards: 1xRS232 | 2xRS232 | 4xRS232 | 8xRS232 | 1xRS422/485 | 2xRS422/485 | 4xRS422/485

Other Brainboxes Ranges: PCI Express | Bluetooth Serial Adapter | Ethernet to Serial Adapter | PCMCIA Serial Card | ExpressCard Serial Adapter | USB to Serial

www.brainboxes.com

sales@brainboxes.com