



一、Electrical charactor:

- (1) 100% Open & Short Testing
- (2) Withstanding Voltage:DC 300V, 0.01s
- (3) Insulation impedance: $\cong 10M\Omega$
- (4) Conduction impedance: $\leq 0.4\Omega$

二、Rated voltage:5V, Current:3A
Rated voltage:9V, Current:2A

5	ZTPE-101C60	MOLDED	TPE插頭料, 黑色, 85A (45P), UL94-HB, 符合ROHS+HF	N/A	KG
4	PLASTIC-086	MOLDED	LD-PE, 透明	N/A	KG
3	ZTC01M02SPT1	SHIELD	TYPE C EMI Shell, SUS304, T=0.25mm, 鍍銀, (L=13.90*H3.60*W9.00), 帶柳爪.	2	PC
2	ZTC22MG024SX01Z0	CONN	TYPE C/M, 24pin, pin針鍍金, 黑色膠芯, 外殼鍍銀, 一體拉伸式, 超薄款	2	PC
1	C000020C11L-4C	CABLE	USB2.0 30AWG/2C+30AWG/1C+20AWG/1C+F+EAB OD:4.0mmTPE 黑色	2.0	M
ITEM	PART No.	NAME	DESCRIPTION	Q' TY	UNIT

MATERIAL SPECIFICATION

△4	△3	△2	△1	DRAWN BY	CHECKED BY	APPROVED BY	CONFIRMED BY	DESCRIPTION	瀚荃股份有限公司 CviLux Corporation		CUST. CODE
								TYPE CM TO CM Cable ASSY	DRAWING No.	CviLux P/N	CUSTOMER P/N
SYM	NAME	DATE	REVISIONS					SHEET: 1 OF 1	D000073A	DH-20UE0064-NH	