

8-Port Industrial Ethernet Switches | IDS-108FE

perle.com/products/switches/ids-108fe-8-port-unmanaged-industrial-ethernet-switch.shtml

IDS-108FE Industrial Ethernet Switches

8-port Compact DIN Rail Switches

- 8 x RJ45 ports with 10/100 Mbps on all ports
- Redundant dual power input 12/24/48 VDC
- Reverse polarity protection
- Fan-less design with no moving parts
- -40 to 75C industrial operating temperature support
- QoS (Quality of Service) prioritized messages



Perle IDS-108FE Industrial Ethernet Switches are designed for easy deployment in industrial environments with harsh operating conditions and limited space. Designed to stand up to extreme temperatures, surges, vibrations, and shocks found in industrial automation, infrastructure, transportation, security, oil and gas, and mining the IDS-108FE Switches are economical easy-to-use devices, that provide essential industrial Ethernet networking functionality.

These unmanaged switches support 9 to 55VDC redundant power input and provide a relay alarm for power failure. The full/half-duplex auto-negotiation and auto MDI/MDIX operation simplifies installation and setup for convenient connection of a variety of network devices. And, QoS support allows for traffic prioritization and effective management of resources.

For automation and industrial control systems using EtherNet/IP, these rugged, DIN rail mountable switches with metal housing provides security and easy installation (mounting kit is included).

Hardware & Technical Specifications: IDS-108FE Industrial Ethernet Switches

Interfaces

RJ45	8 x RJ45 ports for 10/100Base-TX up to 100 meters (328 ft) Auto-negotiation Auto-MDI/MDIX-crossover for use with either crossover over straight-through cable types Ethernet isolation 1500 V
Alarm Contact	One relay output with current 0.5A@30V

Power	
Dual Power Input	12/24/48VDC (9-55VDC)
Power Consumption	3.40W max
Maximum Current Consumption @ 24VDC	0.06A @ 24VDC
Power Connector	7-Pin Removable Terminal Block
Overload Current Protection	2A fuse provides overload current protection
Reverse Polarity Protection	The positive and negative inputs can be reversed providing safe and simple power connectivity.
Switch Properties	
Standards	IEEE 802.3 10BASE-T
	IEEE 802.3u 100BASE-TX/FX
	IEEE 802.3az Energy Efficient Ethernet
	IEEE 802.1p Quality of Service (QoS)
Processing Type	Store-and-Forward
	Auto Negotiation
	Half-duplex back-pressure and IEEE 802.3x full-duplex flow control
	Auto MDI/MDIX
MAC Address Table Size	2K
Packet Buffer Memory	768 Kbps
Jumbo Frame Size	2048 bytes
Forward/Filtering Rate	14,880pps for 10Mbps
	148,810pps for 100Mbps
Indicators	
Power LED 1	This LED is green when power is applied
Power LED 2	This LED is green when power is applied

Fault LED	This LED is red when a fault is detected
RJ45 / SFP Ethernet LED	These LED is solid green for established link and blinks green when activity is detected (per port)

Environmental Specifications

Operating Temperature Ranges	IDS-108FE: -10 to 60°C (14 to 140°F) IDS-108FE-XT: -40 to 75°C (-40 to 167°F)
Storage Temperature Range	-40 to 85°C (-40 to 185°F)
Operating Humidity Range	5% to 90% non-condensing
Storage Humidity Range	5% to 95% non-condensing
Operating Altitude	Up to 3,048 meters (10,000 feet)
Chassis	Metal with an IP40 ingress protection rating
Din Rail Mountable	DIN Rail attachment included. Mounts to standard 35 mm DIN rail in accordance with DIN EN 60175.
Maximum Heat Output	11.594 BTU/Hr
MTBF	11705657 hours MTBF Calculation model based on MIL-HDBK-217-FN2 @ 25°C

Product Weight and Dimensions

Weight	0.336 Kg, 0.74 lbs
Dimensions	45x75x100mm (W x D x H) (1.77"x2.95"x3.94")

Packaging

Shipping Weight	336g (0.74lbs)
Shipping Dimensions	45x75x100mm, 1.77"x2.95"x3.94" (W x D x H)
Contents Shipped	Industrial Ethernet Switch with DIN Rail attachment Terminal block Installation guide

Standards and Certifications

Safety UL 61010

FCC Part 15 Class A

VCCI Class A

EMC Emissions EN 61000-6-4

ICES-003

EN 55032

EN 61000-6-2

EN 61000-4-2 (ESD)

EEN 61000-4-3 (Radiated RFI)

EMC Immunity EN 61000-4-4 (Burst)

EN 61000-4-5 (Surge)

EN 61000-4-6 (Induced RFI)

EN 61000-4-8 (Magnetic field)

Industrial EN 50121-4

Environmental Reach, RoHS and WEEE Compliant

ECCN: 5A991

Other HTSUS Number: 8517.62.0020

5 year warranty

IDS-108FE Industrial Ethernet Switches

