Low Charging Clear Zipper Overall Width (OW) STATSHIELD® ATTENTION ESD Shielding Bag Contents Metal In Construction Static Sensitive Handling Precautions Required Length (L) DescoIndustries.com Made in America Lead-free RoHS compliant Bag Date & Lot Code Printed for QC Traceablility Weld Weld Side Weld Seals 3/8 in. (±0.10) Soft Fold Bottom

** Bags are printed (hot stamp or thermal) with an ESD protective symbol and a lot code for traceability. **

High Performance Static

Dissipative Abrasion

Low Charging Static Dissipative Proprietary

Low Charging Static

Dissipative Proprietary Inner Polyethylene Layer

Resistant Coating

Shielding Layer

Polyester Layer

STATSHIELD® METAL-OUT SERIES

Specifications:

Standard Document

ANSI/ESD S541 (ANSI/ESD S20.20) ANSI/FSD S114

Surface Resistance Outer Surface

Discharge Shielding

Length (Inside Dimensions) Light Transmission

Non-corrosive Silicone

Corrosion

Meets Requirements of: ESD Protective Packaging Level 3 Technical Requirements

Test Procedures/Method

ANSI/ESD STM11.11 ANSI/FSD STM11 11 ANSI/ESD STM11.31. EIA 541

Modified Incline Plane Modified Incline Plane

MIL-STD-3010, 1003

ANSI/EIA-541/Appendix E, 1 kV Discharge

Nominal 0.003" (0.0762mm) ±10%

Nominal -0" / + 0.125" Nominal ± 0.125"

Typical Values

40% (Tobias) **ASTM D-1003** >10 lbs MIL-STD-3010, 2065 >10 lbs/in. 375°F, 1/2 sec 60 psi Pass MIL-STD-3010, M3005 Not detected ASTM E168

IPC-TM-650 2.4.1 Pass

No effect on aluminum, copper, silver, Sn-Pb coated foil.

stainless steel, low carbon steel

ANSI/ESD S541 Section 6.2 Outside an EPA

"Transportation of sensitive products outside of an EPA shall require packaging that provides:

- 1. Low charge generation
- 2. Dissipative or conductive materials for intimate contact
- 3. A structure that provides electrostatic discharge shielding."

RoHS, REACH and Conflict Minerals Statement

See the Desco Industries RoHS, REACH, and Conflict Minerals Statement: Regulatory Statement Statshield Bags.pdf

See Protektive Pak's Limited Warranty: ProtektivePak.com/Limted-Warranty

Statshield® and Statfree® are Registered Trademarks of Desco Industries Inc. See Bag Selection Chart Click HERE.

Made in the United States of America

Specifications and procedures subject to change without notice.

Statshield® bags are packaged 100 per package in an oversized shielding bag. See Shielding Bag Storage at TB-7057.

Mixed Unsortable Plastic Scrap Mixed unsortable plastic scrap shall contain assorted plastics of multiple grades that are co-extruded,

bonded or laminated together which are unsortable

into individual grades.

Protektive Pak's bags are recyclable

STATSHIELD® BAG, SHIELDING, METAL-OUT, ZIPPER

PROTEKTIVE PAK

PROTEKTIVE PAK

13520 MONTE VISTA AVENUE, CHINO, CA 91710 PHONE (909) 627-2578 ProtektivePak.com

DRAWING NUMBER 48770

DATE: September 2021

Electrical Properties

 $1 \times 10^4 \text{ to} < 1 \times 10^8 \text{ ohms}$ Inner Surface 1×10^4 to $< 1 \times 10^{11}$ ohms <20 n.J

Charge Generation Teflon: -0.03 nC/sq. in. Quartz: +0.10 nC/sq. in.

<30 volts

Capacitance Probe (to dissipate 1 KV)

Physical Properties:

Film Thickness Width (Inside Dimensions)

Puncture Resistance Heat Seal

Marking Adhesion

Chemical Properties

© 2021 DESCO INDUSTRIES INC