



## Main

|                              |                                                    |
|------------------------------|----------------------------------------------------|
| Range of Product             | Hyde Park                                          |
| Sensor Type                  | Ultrasonic sensor                                  |
| Series name                  | Superprox 900                                      |
| Device short name            | SM952                                              |
| Sensor design                | Cylindrical M30                                    |
| Type of sensing window       | Adjustable                                         |
| Material                     | Plastic                                            |
| Enclosure Material           | ULTEM                                              |
| Front material               | Silicone rubber                                    |
| Type of output signal        | Discrete                                           |
| Discrete output function     | 1 NO                                               |
| ISO thread                   | M30 x 1.5                                          |
| Wiring Technique             | 4-wire                                             |
| [Us] rated supply voltage    | 12...24 V DC overload and short-circuit protection |
| Supply voltage limits        | 10...28 V DC                                       |
| Discrete output type         | NPN                                                |
| Electrical connection        | Male connector M12 4 pins                          |
| Product Specific Application | Dual-level - alarm                                 |

## Complementary

|                                 |                                                          |
|---------------------------------|----------------------------------------------------------|
| [Sn] nominal sensing distance   | 3.28 ft (1 m)                                            |
| [Sd] sensing range              | 0.17...3.28 ft (0.0508...1 m)                            |
| Maximum differential travel     | 0.10 in (2.5 mm)                                         |
| Blind zone                      | 2.01 in (51 mm)                                          |
| Transmission frequency          | 200 kHz                                                  |
| Repeat accuracy                 | 0.87 %                                                   |
| Beam angle                      | 10 °                                                     |
| Minimum size of detected object | Cylinder diameter 1.6 mm - up to 305 mm sensing distance |
| Current Consumption             | 100 mA                                                   |
| Maximum switching current       | 100 mA reverse polarity protection                       |
| Height                          | 1.18 in (30 mm)                                          |
| Width                           | 1.37 in (34.7 mm)                                        |
| Depth                           | 1.18 in (30 mm)                                          |
| Length                          | 3.78 in (96 mm)                                          |
| Net Weight                      | 0.57 lb(US) (0.26 kg)                                    |

## Environment

|                                       |                                  |
|---------------------------------------|----------------------------------|
| Product Certifications                | UL                               |
| Marking                               | CE                               |
| NEMA degree of protection             | NEMA 4X indoor use only)         |
| IP degree of protection               | IP67                             |
| Ambient Air Temperature for Operation | 32...122 °F (0...50 °C)          |
| Ambient Air Temperature for Storage   | -4...176 °F (-20...80 °C)        |
| Relative humidity                     | 100 % without condensation       |
| Vibration resistance                  | +/-1 mm 10...55 Hz)IEC 60068-2-6 |

|                                      |                                          |
|--------------------------------------|------------------------------------------|
| Shock resistance                     | 30 gn in all 3 axes 11 ms IEC 60068-2-27 |
| Resistance to electromagnetic fields | 9.14 V/m (10 V/m) level 3 IEC 61000-4-3  |
| Resistance to fast transients        | 1 kV level 3 IEC 61000-4-4               |

### Ordering and shipping details

|                       |                                  |
|-----------------------|----------------------------------|
| Category              | 22490-SENSORS-ULTRASONIC (XX5,6) |
| Discount Schedule     | DS2                              |
| GTIN                  | 03389119119344                   |
| Nbr. of units in pkg. | 1                                |
| Package weight(Lbs)   | 0.26 lb(US) (0.12 kg)            |
| Returnability         | No                               |
| Country of origin     | US                               |

### Offer Sustainability

|                           |                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation          | <a href="#">REACH Declaration</a>                                                                                                                                                                                                                                                                                                                                                 |
| EU RoHS Directive         | Not applicable, out of EU RoHS legal scope                                                                                                                                                                                                                                                                                                                                        |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|