

## Sleeve housing for coupler connector - RC-0000007300 - 1592626

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Sleeve housing for coupler connector, straight, Screw locking, M23, Shielded: No, Cable cross section: 10 mm...14 mm



### Key commercial data

Packing unit	1 1
Weight per Piece (excluding packing)	68.97 GRM
Custom tariff number	85389099
Country of origin	Germany

### Technical data

#### General

Note	Order information Order contact inserts and cable clamping separately
Type of locking	Screw locking
Contact connection method	Crimp connection
Type of contacts	Socket
Conductor entry	10 mm ... 14 mm

#### Ambient conditions

Ambient temperature	-20 °C ... 125 °C
Degree of protection	IP65

#### Material

Housing material	Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Gasket and O-ring material	FPM

#### Specifications according to DIN EN 61984:2001

Installation height max.	2000 m
--------------------------	--------

# Sleeve housing for coupler connector - RC-00000007300 - 1592626

## Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260708
eCl@ss 7.0	27440312
eCl@ss 8.0	27440312



## ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC000437
ETIM 5.0	EC000437

## UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404

## Drawings



## Sleeve housing for coupler connector - RC-0000007300 - 1592626

Dimensioned drawing

