

# CA-12S2S8A80DN - Cable connector



1621436

<https://www.phoenixcontact.com/us/products/1621436>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Cable connector, series: CA, straight, shielded: yes, Screw locking mechanism, No. of pos. : 12, Direction of rotation: Counter direction, contact connection type: Socket, Crimp connection, cable diameter range: 3 mm ... 14.5 mm, coding: S, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1244400

## Commercial data

Item number	1621436
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	AB33
Product key	ABRAEA
GTIN	4046356932530
Weight per piece (including packing)	93.5 g
Weight per piece (excluding packing)	86.71 g
Customs tariff number	85366990
Country of origin	DE

# CA-12S2S8A80DN - Cable connector



1621436

<https://www.phoenixcontact.com/us/products/1621436>

## Technical data

### Product properties

Product type	Circular connector (cable-side)
--------------	---------------------------------

### Connector

#### Insulating body

Coding	S
Connection method	Crimp connection
Contact switching type	Socket
Application	Signal
Number of positions	12
Direction of rotation	Counter direction
Connection profile	12
Contact diameter	1 mm
<b>Power contacts</b>	
Rated current	8 A
Rated voltage	48 V AC 74 V DC
Rated surge voltage	1.5 kV
Overvoltage category	III
Degree of pollution	3

#### Housing

Housing material	Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Type of locking	Screw locking mechanism
Pg screw connection	none
Degree of protection (plugged in)	IP67
Thread type	M23

#### Seal

External cable diameter	3 mm ... 14.5 mm
Seal material	NBR


# CA-12S2S8A80DN - Cable connector

1621436

<https://www.phoenixcontact.com/us/products/1621436>


## Drawings

Schematic diagram



Contact chamber numbering (view of plug-in side), socket counter direction

Dimensional drawing



# CA-12S2S8A80DN - Cable connector



1621436

<https://www.phoenixcontact.com/us/products/1621436>

## Classifications

### ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116

### ETIM

ETIM 8.0	EC002635
----------	----------

### UNSPSC

UNSPSC 21.0	39121400
-------------	----------

# CA-12S2S8A80DN - Cable connector



1621436

<https://www.phoenixcontact.com/us/products/1621436>

## Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

# CA-12S2S8A80DN - Cable connector

1621436

<https://www.phoenixcontact.com/us/products/1621436>

## Accessories

### RC-Z2058 - Protective cap

1604223

<https://www.phoenixcontact.com/us/products/1604223>



Plastic protection cap for connectors with M23 knurled nut

---

### RC-Z2468 - Protective cap

1611796

<https://www.phoenixcontact.com/us/products/1611796>



Plastic protection cap, antistatic, for connectors with M23 knurled nut

## CA-12S2S8A80DN - Cable connector

1621436

<https://www.phoenixcontact.com/us/products/1621436>



## CA-Z0077 - Metal protective cap

1627224

<https://www.phoenixcontact.com/us/products/1627224>



Metal protective cap, degree of protection: IP67, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1245447

---

## SF-Z0028 - Torque screwdriver

1607456

<https://www.phoenixcontact.com/us/products/1607456>



Torque screwdriver, series: RC

# CA-12S2S8A80DN - Cable connector

1621436

<https://www.phoenixcontact.com/us/products/1621436>



## SF-Z0027 - Hook wrench

1607455

<https://www.phoenixcontact.com/us/products/1607455>



Hook wrench, series: RC

---

## RF-Z0014 - Color-coding

1620588

<https://www.phoenixcontact.com/us/products/1620588>



Color-coding, color: green



# CA-12S2S8A80DN - Cable connector

1621436

<https://www.phoenixcontact.com/us/products/1621436>



## RF-Z0015 - Color-coding

1620592

<https://www.phoenixcontact.com/us/products/1620592>

Color-coding, color: orange



---

## RF-Z0016 - Color-coding

1620593

<https://www.phoenixcontact.com/us/products/1620593>

Color-coding, color: black



# CA-12S2S8A80DN - Cable connector

1621436

<https://www.phoenixcontact.com/us/products/1621436>



## RC-22S2000 - Crimp contact

1603327

<https://www.phoenixcontact.com/us/products/1603327>



Crimp contact, Socket, rolled, Single contact, contact diameter: 1 mm, crimp range: 0.22 mm<sup>2</sup> ... 0.56 mm<sup>2</sup>, Single contact, Item is lead-free in accordance with RoHS II without Exemption 6c (Pb <0.1%)

---

## RC-12S2000 - Crimp contact

1599600

<https://www.phoenixcontact.com/us/products/1599600>



Crimp contact, Socket, turned, Single contact, contact diameter: 1 mm, crimp range: 0.14 mm<sup>2</sup> ... 0.56 mm<sup>2</sup>, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1241093

# CA-12S2S8A80DN - Cable connector

1621436

<https://www.phoenixcontact.com/us/products/1621436>



## RF-Z0003 - Square mounting flange

1607905

<https://www.phoenixcontact.com/us/products/1607905>



Square mounting flange, Axial seal, 4xM3, flange dimensions: 35 mm x 35 mm, series: RF, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1242369

---

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)