

## Introduction

The GT Series Rackmount UPS provides high quality power protection in a cost-effective package. The GT Series is a true VFI (Voltage and Frequency Independent), **on-line double conversion**, high-performance device.

The UPS is designed to support and protect mission critical applications, and the bypass mode provides high reliability against mains power disturbances. All GE GT UPS's are microprocessor- controlled, with **extended optional battery pack** runtime options available.

The GT Series is designed especially for typical rack mount demands, including long backup times and high ambient temperatures, but can be a stand-alone unit for increased versatility.

## Benefits

- > Rack design provides application versatility
- > UPS height maximizes rack space
- > Easy plug-in connection of battery packs for extended runtime
- > Simple to install and operate
- > Fully compliant with international standards for VFI (IEC 62040-3) operation, providing full power protection for demanding critical applications
- > Programmable switch-off for less critical loads to maximize uptime of critical devices (load shedding)
- > Integrated slot for SNMP plug-in card, potential-free relay contacts and RS-232/contact interface, providing maximum flexibility

## Performance Features

- > **High input power factor** (>.97) and **low input distortion** prevents disturbances to other electrical equipment, eliminating the need for costly filters or oversized feeders
- > **Compact footprint**, easily transportable, robustly designed system with low audible noise, suitable for both office and industrial environments
- > Utilizes high-frequency PWM (Pulse Width Modulation) digital control technique, resulting in extremely **low output distortion** and **fast transient response**, eliminating the need to oversize the UPS
- > Robustly designed to handle **short-circuit, high overload and overheating** conditions, reducing maintenance and service costs
- > GT Series **High Crest Factor** (3:1) capability makes it ideal for computer loads, while eliminating the need to oversize the UPS
- > **Very wide AC-input voltage** capability minimizes the need to switch to batteries, resulting in increased battery life
- > **On-line double conversion** technology eliminates power reliability problems
- > Automatic **internal bypass**
- > **UPS management software** facilitates operation and maintenance of the UPS

# 1000-3000VA 19" Rackmount

## GT Series Uninterruptible Power Supply (UPS)



## Technical Specifications – UL approved

Models	GT1000R	GT1500R	GT2200R	GT3000R
Rating (VA/W)	1000 / 800	1500 / 1200	2200 / 1760	3000 / 2400
Battery (V/Ah)	36 / 7	48 / 7	48 / 9	72 / 9
50% Load	21 min.	12 min.	15 min.	14 min.
100% Load	6 min.	4 min.	5 min.	5 min.
Option for Additional Batteries **	Yes	Yes	Yes	Yes
Enclosure (Table 1)	C	D	D	E
Net Wgt Incl. Batteries (kg / lbs)	19 / 42	24 / 52.8	24 / 52.8	34 / 74.9
Input Voltage @ 100% load (VAC)	80-138	80-138	80-138	80-138
Input Frequency (Hz)*	50 / 60	50 / 60	50 / 60	50 / 60
Output Voltage	100 / 110	100 / 110	100 / 110	100 / 110
	120	120	120	120
Output Frequency (Hz) *	50 / 60	50 / 60	50 / 60	50 / 60
Outlet (Qty) Type	(6) NEMA 5-15R	(6) NEMA 5-15R	(4) NEMA 5-20R (1) NEMA L5-20R	(4) NEMA 5-15R (4) NEMA 5-20R (1) NEMA 5-30R
SNMP Compatibility		Yes		
Core Voltage		120		
PWM (Pulse Width Modulation)		Yes		
Maintenance Bypass		Yes		
Internal Batteries		Yes		
Input Performance Range	Voltage (-33 to +17%); Frequency (55 to 65 Hz)			
Output Performance	<ul style="list-style-type: none"> <li>Output THD Load Non-Linear (&lt; 6%); Linear (&lt; 3%)</li> <li>Voltage Regulation Load Static (2%); 0-100% Step (8%)</li> </ul>			
Overload Capability	150% for 30 Seconds			
Efficiency	> 87%			
Communications Interface	RS-232, Plug and Play, open collector alarm contacts			
Color	Front bezel: Aluminum Grey (RAL 9006); Cabinet: White (RAL 9003)			
Operating Temperature	32° F - 104° F (0° C - 40° C)			
Relative Humidity	95% non-condensing			
Audible Noise	(Table 2)			
Certifications	UL 1778, CSA22.2-107, IEEE 62.41 CAT. A Lightning Safety			
EMC	FCC Class B (1kVA), FCC Class A, CISPR PUB. 22 Class A			
Enclosure	NEMA 1			
Warranty	24 months after seller's shipment to customer			

\* Auto Selectable

\*\* Refer to Product Description publication for runtimes




**Table 1**

	Height	Width	Depth
Enclosure C	3.5" (8.9 cm)	17.3" (43.9 cm)	17.7" (45 cm)
Enclosure D	3.5" (8.9 cm)	17.3" (43.9 cm)	20.7" (52.6 cm)
Enclosure E	5.2" (13.2 cm)	17.3" (43.9 cm)	19.8" (50.3 cm)

**Table 2**

Audible Noise at Unit Front	
1kVA	40dBA @ 3.3 feet (1 meter)
1.5 & 2kVA	45dBA @ 3.3 feet (1 meter)
3kVA	47dBA @ 3.3 feet (1 meter)

Represented by:



GE Energy – Digital Energy  
830 W 40th Street  
Chicago, IL 60609 USA  
800 637 1738  
[www.gepowerquality.com](http://www.gepowerquality.com)

Information subject to change without notice. Please verify all details with GE.  
© 2010 General Electric Company  
All Rights Reserved

GEA-D2006 (10/10)

