

## AMP | AMP CPC

TE Internal #: 206151-2

Circular Power Connectors, Housing, 600 VDC, Wire-to-Wire, 37

Position, Wire & Cable, Receptacle, Pin, Power & Signal, Black, All

Plastic, AMP CPC

View on TE.com >



Connectors > Power Connectors > Circular Power > Circular Power Connectors > Cable/Panel Mount Connector, CPC Series 1











Connector Product Type: Housing

Operating Voltage: 600 VDC

Connector System: Wire-to-Wire

Number of Positions: 37

Sealable: No

All Cable/Panel Mount Connector, CPC Series 1 (57)

## **Features**

### **Product Type Features**

Connector Product Type	Housing
Connector System	Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Connector & Housing Type	Receptacle
Circular Connector Shell Type	All Plastic

## **Configuration Features**

Reverse Numbering	Without
Number of Positions	37
Number of Power Positions	0
Number of Signal Positions	37

### **Electrical Characteristics**



Operating Voltage	600 VAC
Contact Features	
Reverse Gender	No
Contact Type	Pin
Contact Protection	With
Mechanical Attachment	
Mating Alignment Type	Keyed
Mating Alignment	With
Mating Retention Type	Threaded Coupling
Thread Size	1-3/8 - 18 UNEF-2A
Polarization Code	A
Connector Mounting Type	Cable Mount (Free-Hanging)
Mating Retention	With
Panel Mount Feature	Without
Housing Features	
Body Orientation	Straight
Body Orientation  Housing Color	Straight Black
Housing Color	Black
Housing Color  Housing Material  Circular Connector Shell Size	Black Thermoplastic
Housing Color  Housing Material  Circular Connector Shell Size	Black Thermoplastic
Housing Color  Housing Material  Circular Connector Shell Size  Usage Conditions	Black Thermoplastic 23
Housing Color  Housing Material  Circular Connector Shell Size  Usage Conditions  Operating Temperature Range  Fluid Resistance	Black Thermoplastic 23 -55 - 105 °C[-67 - 221 °F]
Housing Color  Housing Material  Circular Connector Shell Size  Usage Conditions  Operating Temperature Range  Fluid Resistance	Black Thermoplastic 23 -55 - 105 °C[-67 - 221 °F]
Housing Color  Housing Material  Circular Connector Shell Size  Usage Conditions  Operating Temperature Range  Fluid Resistance  Operation/Application	Black Thermoplastic 23  -55 – 105 °C[-67 – 221 °F] None
Housing Color  Housing Material  Circular Connector Shell Size  Usage Conditions  Operating Temperature Range  Fluid Resistance  Operation/Application  Circuit Application  Shielded	Black Thermoplastic 23  -55 – 105 °C[-67 – 221 °F] None  Power & Signal
Housing Color  Housing Material  Circular Connector Shell Size  Usage Conditions  Operating Temperature Range  Fluid Resistance  Operation/Application  Circuit Application  Shielded	Black Thermoplastic 23  -55 – 105 °C[-67 – 221 °F] None  Power & Signal
Housing Color  Housing Material  Circular Connector Shell Size  Usage Conditions  Operating Temperature Range  Fluid Resistance  Operation/Application  Circuit Application  Shielded  Industry Standards	Black Thermoplastic  23  -55 – 105 °C[-67 – 221 °F]  None  Power & Signal  No
Housing Color Housing Material Circular Connector Shell Size Usage Conditions Operating Temperature Range Fluid Resistance Operation/Application Circuit Application Shielded Industry Standards UL Flammability Rating	Black Thermoplastic  23  -55 – 105 °C[-67 – 221 °F]  None  Power & Signal  No

## **Product Compliance**



#### For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts



CPC Cable Clamps



TE Part # 206150-1 CPC PLUG ASSEMBLY SIZE 23-37



TE Part # 207299-4 FLANGE PLUG





TE Part # 207055-1
EXTENDER BACK SHELL



TE Part # 206150-2 CPC PLUG,SZ 23-37,SMALL PACK



TE Part # 6-2407269-4
CAP, CPC, SIZE 23 RECP, YELLOW









## Also in the Series | AMP CPC



Circular Connector Adapters(7)



Circular Connector Caps & Covers(16)



Circular Connector Hardware(3)



Circular Connector Keying Plugs(2)



Circular Power Connectors(459)



Connector Backshells(56)



Connector Seals & Cavity Plugs(36)



Connector Strain Relief(6)



Insertion & Extraction Tools(1)



Power Contacts(6)




Sealing Sleeves(2)

# Customers Also Bought











TE Part #2-968696-3

4POS MQS TAB COD B

TE Part #881572-4

FUSE CONTACT BUS BA

TE Part #1599381-1

CHRISTMAS TREE

### **Documents**

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_206151-2\_AG.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_206151-2\_AG.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_206151-2\_AG.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## Datasheets & Catalog Pages

AMP Circular Connectors for Commercial Signal & Power Applications

English

**Product Specifications** 

**Application Specification** 

English

**Instruction Sheets** 

Instruction Sheet (U.S.)

English

Agency Approvals

**UL Report** 

English