

International **IR** Rectifier

IRF7521D1PbF


FETKY™ MOSFET / Schottky Diode

- Co-packaged HEXFET® Power MOSFET and Schottky Diode
- N-Channel HEXFET
- Low V_F Schottky Rectifier
- Generation 5 Technology
- Micro8™ Footprint
- Lead-Free

Description


The **FETKY™** family of co-packaged HEXFETs and Schottky diodes offer the designer an innovative board space saving solution for switching regulator applications. Generation 5 HEXFETs utilize advanced processing techniques to achieve extremely low on-resistance per silicon area. Combining this technology with International Rectifier's low forward drop Schottky rectifiers results in an extremely efficient device suitable for use in a wide variety of portable electronics applications like cell phone, PDA, etc.

The new Micro8™ package, with half the footprint area of the standard SO-8, provides the smallest footprint available in an SOIC outline. This makes the Micro8™ an ideal device for applications where printed circuit board space is at a premium. The low profile (<1.1mm) of the Micro8™ will allow it to fit easily into extremely thin application environments such as portable electronics and PCMCIA cards.



Top View

$V_{DSS} = 20V$
$R_{DS(on)} = 0.135\Omega$
Schottky $V_f = 0.39V$



Micro8™

Absolute Maximum Ratings ($T_A = 25^\circ C$ unless otherwise noted)

Parameter	Maximum	Units
$I_D @ T_A = 25^\circ C$	Continuous Drain Current, $V_{GS} @ 4.5V$	A
$I_D @ T_A = 70^\circ C$		
I_{DM}	Pulsed Drain Current ①	
$P_D @ T_A = 25^\circ C$		
$P_D @ T_A = 70^\circ C$	Power Dissipation	W
	Linear Derating Factor	mW/°C
V_{GS}	Gate-to-Source Voltage	V
dv/dt	Peak Diode Recovery dv/dt ②	V/ns
T_J, T_{STG}	Junction and Storage Temperature Range	°C

Thermal Resistance Ratings

Parameter	Maximum	Units
$R_{θJA}$	100	°C/W

Notes:

- ① Repetitive rating; pulse width limited by maximum junction temperature (see figure 9)
- ② $I_{SD} \leq 1.7A$, $di/dt \leq 66A/\mu s$, $V_{DD} \leq V_{(BR)DSS}$, $T_J \leq 150^\circ C$
- ③ Pulse width $\leq 300\mu s$; duty cycle $\leq 2\%$
- ④ Surface mounted on FR-4 board, $t \leq 10sec$.

MOSFET Electrical Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Conditions
$V_{(\text{BR})\text{DSS}}$	Drain-to-Source Breakdown Voltage	20	—	—	V	$V_{\text{GS}} = 0\text{V}$, $I_D = 250\mu\text{A}$
$R_{\text{DS}(\text{on})}$	Static Drain-to-Source On-Resistance	—	0.085	0.135	Ω	$V_{\text{GS}} = 4.5\text{V}$, $I_D = 1.7\text{A}$ ③
		—	0.12	0.20		$V_{\text{GS}} = 2.7\text{V}$, $I_D = 0.85\text{A}$ ③
$V_{\text{GS}(\text{th})}$	Gate Threshold Voltage	0.70	—	—	V	$V_{\text{DS}} = V_{\text{GS}}$, $I_D = 250\mu\text{A}$
g_{fs}	Forward Transconductance	2.6	—	—	S	$V_{\text{DS}} = 10\text{V}$, $I_D = 0.85\text{A}$
I_{DSS}	Drain-to-Source Leakage Current	—	—	1.0	μA	$V_{\text{DS}} = 16\text{V}$, $V_{\text{GS}} = 0\text{V}$
		—	—	25		$V_{\text{DS}} = 16\text{V}$, $V_{\text{GS}} = 0\text{V}$, $T_J = 125^\circ\text{C}$
I_{GSS}	Gate-to-Source Forward Leakage	—	—	100	nA	$V_{\text{GS}} = 12\text{V}$
	Gate-to-Source Reverse Leakage	—	—	-100		$V_{\text{GS}} = -12\text{V}$
Q_g	Total Gate Charge	—	5.3	8.0	nC	$I_D = 1.7\text{A}$
Q_{gs}	Gate-to-Source Charge	—	0.84	1.3		$V_{\text{DS}} = 16\text{V}$
Q_{gd}	Gate-to-Drain ("Miller") Charge	—	2.2	3.3		$V_{\text{GS}} = 4.5\text{V}$, See Fig. 6 ③
$t_{\text{d}(\text{on})}$	Turn-On Delay Time	—	5.7	—	ns	$V_{\text{DD}} = 10\text{V}$
t_r	Rise Time	—	24	—		$I_D = 1.7\text{A}$
$t_{\text{d}(\text{off})}$	Turn-Off Delay Time	—	15	—		$R_G = 6.0\Omega$
t_f	Fall Time	—	16	—		$R_D = 5.7\Omega$, ③
C_{iss}	Input Capacitance	—	260	—	pF	$V_{\text{GS}} = 0\text{V}$
C_{oss}	Output Capacitance	—	130	—		$V_{\text{DS}} = 15\text{V}$
C_{rss}	Reverse Transfer Capacitance	—	61	—		$f = 1.0\text{MHz}$, See Fig. 5

MOSFET Source-Drain Ratings and Characteristics

	Parameter	Min.	Typ.	Max.	Units	Conditions
I_S	Continuous Source Current(Body Diode)	—	—	1.3	A	
I_{SM}	Pulsed Source Current (Body Diode)	—	—	14		
V_{SD}	Body Diode Forward Voltage	—	—	1.2	V	$T_J = 25^\circ\text{C}$, $I_S = 1.7\text{A}$, $V_{\text{GS}} = 0\text{V}$
t_{rr}	Reverse Recovery Time (Body Diode)	—	39	59	ns	$T_J = 25^\circ\text{C}$, $I_F = 1.7\text{A}$
Q_{rr}	Reverse RecoveryCharge	—	37	56	nC	$dI/dt = 100\text{A}/\mu\text{s}$ ③

Schottky Diode Maximum Ratings

	Parameter	Max.	Units	Conditions	
$I_{\text{F(av)}}$	Max. Average Forward Current	1.9	A	50% Duty Cycle. Rectangular Wave, $T_A = 25^\circ\text{C}$	
		1.4		$T_A = 70^\circ\text{C}$	
I_{SM}	Max. peak one cycle Non-repetitive Surge current	120	A	5μs sine or 3μs Rect. pulse	Following any rated load condition & with V_{RRM} applied
		11		10ms sine or 6ms Rect. pulse	

Schottky Diode Electrical Specifications

	Parameter	Max.	Units	Conditions	
V_{FM}	Max. Forward voltage drop	0.50	V	$I_F = 1.0\text{A}$, $T_J = 25^\circ\text{C}$	
		0.62		$I_F = 2.0\text{A}$, $T_J = 25^\circ\text{C}$	
		0.39		$I_F = 1.0\text{A}$, $T_J = 125^\circ\text{C}$	
		0.57		$I_F = 2.0\text{A}$, $T_J = 125^\circ\text{C}$.	
I_{RM}	Max. Reverse Leakage current	0.02	mA	$V_R = 20\text{V}$	$T_J = 25^\circ\text{C}$
		8			$T_J = 125^\circ\text{C}$
C_t	Max. Junction Capacitance	92	pF	$V_R = 5\text{Vdc}$ (100kHz to 1 MHz) 25°C	
dv/dt	Max. Voltage Rate of Change	3600	V/ μs	Rated V_R	

(HEXFET is the reg. TM for International Rectifier Power MOSFET's)

Power Mosfet Characteristics




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. Typical Transfer Characteristics




Fig 4. Normalized On-Resistance
Vs. Temperature

IRF7521D1PbF

Power Mosfet Characteristics

International
IR Rectifier




Fig 5. Typical Capacitance Vs.
Drain-to-Source Voltage




Fig 6. Typical Gate Charge Vs.
Gate-to-Source Voltage




Fig 7. Typical Source-Drain Diode
Forward Voltage




Fig 8. Maximum Safe Operating Area

Power Mosfet Characteristics




Fig 9. Maximum Effective Transient Thermal Impedance, Junction-to-Ambient




Fig 10. Typical On-Resistance Vs. Drain Current

www.irf.com




Fig 11. Typical On-Resistance Vs. Gate Voltage

5

IRF7521D1PbF

International
IR Rectifier

Schottky Diode Characteristics




Fig. 12 -Typical Forward Voltage Drop Characteristics




Fig. 13 - Typical Values of Reverse Current Vs. Reverse Voltage





Fig.14 - Maximum Allowable Ambient Temp. Vs. Forward Current


Micro8 Package Outline

Dimensions are shown in millimeters (inches)



Micro8 Part Marking Information

EXAMPLE: THIS IS AN IRF7501



WW = (1-26) IF PRECEDED BY LAST DIGIT OF CALENDAR YEAR

YEAR	Y	WORK WEEK	W
2001	1	01	A
2002	2	02	B
2003	3	03	C
2004	4	04	D
2005	5		
2006	6		
2007	7		
2008	8		
2009	9		
2010	0	24	X
		25	Y
		26	Z

WW = (27-52) IF PRECEDED BY A LETTER


YEAR	Y	WORK WEEK	W
2001	A	27	A
2002	B	28	B
2003	C	29	C
2004	D	30	D
2005	E		
2006	F		
2007	G		
2008	H		
2009	J	50	X
2010	K	51	Y
		52	Z

IRF7521D1PbF

International
IR Rectifier


Micro8 Tape & Reel Information

Dimensions are shown in millimeters (inches)



NOTES:

1. OUTLINE CONFORMS TO EIA-481 & EIA-541.
2. CONTROLLING DIMENSION : MILLIMETER.



NOTES :

1. CONTROLLING DIMENSION : MILLIMETER.
2. OUTLINE CONFORMS TO EIA-481 & EIA-541.

Data and specifications subject to change without notice.
This product has been designed and qualified for the Consumer market.
Qualification Standards can be found on IR's Web site.

International
IR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7903

Visit us at www.irf.com for sales contact information. 05/04
www.irf.com