



® TRADEMARK OF RAYCHEM CORP.

REVISIONS		
LTR	DESCRIPTION	DATE
A	REVISED PER ECN T-17674	92 Aug 16

If this document is printed it becomes uncontrolled.  
Check with the web for latest revision.

NOTES:

1. MATERIAL:

I-A INSULATION SLEEVE; HEAT SHRINKABLE, RADIATION CROSSLINKED MODIFIED POLYVINYLIDENE FLUORIDE, TRANSPARENT BLUE.

I-B SOLDER PREFORM; SOLDER TYPE: Sn 63  
FLUX TYPE: RA  
PER QQ-S-571

I-C MELTABLE INSERTS; LOW OUTGASSING, IMMERSION RESISTANT THERMOPLASTIC.

2. THIS SLEEVE IS DESIGNED TO ATTACH 20 THROUGH 26 GAGE TIN, NICKEL OR SILVER PLATED CONDUCTORS TO TERMINALS OF A **Raychem** MTC100 SERIES WAFER. CONSULT FACTORY FOR 18 GAGE APPLICATIONS.

⚠ WEIGHT: .0001 lbs. [0.045g] MAX.

SPECIFICATION CONTROL DRAWING © Raychem Corporation 1983

DRAWN	CACELA	11-16-83	<b>Raychem</b>	RAYCHEM CORPORATION 300 CONSTITUTION DRIVE MENLO PARK, CALIFORNIA 94025	
CHECKED	JB			TITLE	
APPROVED	<i>gitan</i>	11-29-83	SOLDERSLEEVE <sup>®</sup> WIRE TERMINATOR		
APPROVED	<i>Lawson</i>	12-2-83	WITH OVAL ENTRY		
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. METRIC DIMENSIONS ARE IN PARENTHESIS			TEMP. RATING 125°C MTC100 SERIES		
SIZE		CODE IDENT. NO.	DWG. NO.		
B		06090	CTA-0068		
DO NOT SCALE THIS DRAWING		WEIGHT	/3		SHEET 1 OF 1