

https://www.phoenixcontact.com/us/products/0203328



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Insertion bridge, pitch: 10 mm, number of positions: 3, color: gray



#### Commercial data

Item number	0203328
Packing unit	1 pc
Minimum order quantity	10 pc
Sales key	BE19
Product key	BE1Z2X
Catalog page	Page 344 (CL-2009)
GTIN	4017918098339
Weight per piece (including packing)	5.27 g
Weight per piece (excluding packing)	4.86 g
Customs tariff number	85366990
Country of origin	PL



https://www.phoenixcontact.com/us/products/0203328



#### Technical data

#### Product properties

Product type	Insertion bridge
Number of positions	3
Pitch	10 mm

#### Dimensions

Pitch	10 mm

#### Material specifications

Color	gray
Material	Copper
Flammability rating according to UL 94	V0
Insulating material	PA

#### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-60 °C 105 °C
Ambient temperature (storage/transport)	-25 °C 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C 70 °C
Ambient temperature (actuation)	-5 °C 70 °C
Permissible humidity (storage/transport)	30 % 70 %

#### Mounting

Marintina tima	Communication
Mounting type	Screw mounting



https://www.phoenixcontact.com/us/products/0203328



### Classifications

#### **ECLASS**

	ECLASS-11.0	27141140
	ECLASS-12.0	27141140
	ECLASS-13.0	27250303
ET	ТМ	

EC000489

#### **UNSPSC**

ETIM 8.0

UNSPSC 21.0	39121400

0203328

https://www.phoenixcontact.com/us/products/0203328



## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com