

500W AC-DC Medical or Industrial Power Supplies

Features

- ◆ 360W Convection rating
- ◆ High Efficiency
- ◆ IEC60601-1 or IEC60950-1 certifications
- ◆ ORing FET & Current Share
- ◆ Dual input fuses



Key Market Segments & Applications



Specifications		
Model	CSS500	
Input Voltage range	-	90 - 264VAC (47 - 63Hz)
Inrush Current	A	<50A maximum at 230VAC input, 25°C ambient cold start
Input Current (115/230VAC)	A	6 / 3A
Power Factor Correction	-	Meets EN61000-3-2, >0.9
Leakage Current	µA	<300µA 264VAC 63Hz
Hold Up Time (Typ)	ms	20ms at 115VAC input, 360W loading
Temperature Coefficient	-	±0.04%/°C
Voltage Accuracy	%	±1% at 60% load
Adjustment Range	%	None
Regulation	-	Load Regulation ±1%, Line Regulation ±0.5%
Ripple & Noise	%	1% peak to peak (5Vsb also)
Overcurrent Protection	-	110 - 150%
Overvoltage Protection	V	110 - 130% of nominal (Cycle input power or use remote on/off to reset)
Overtemperature Protection	-	Yes (Cycle input power or use remote on/off to reset)
Remote On/Off	-	Unit on: Floating or high 3.5 - 5.25V, Unit off: Low or <0 - 0.5V
Remote Sense	-	Yes
Efficiency	%	87% to 92%, model & input dependant
Standby Voltage	-	5V 1A (5V 0.25A when convection cooled or when inhibit is activated)
Fan Output	-	12V 1A
Current Share	-	Single wire, up to 4 units can be shared within 10% accuracy at full load
DC Good & Fan Fail Signals	-	Both Low on Fail
ORing FET	-	Yes, for redundant operation
Operating Temperature	°C	Convection (U channel): 0 to +70°C, derate linearly to 35% load from 40 to 70°C Forced air (or internal fan): 0 to +70°C, derate linearly to 50% load from 50 to 70°C
Storage Temperature	°C	-10 to +85°C
Humidity (non condensing)	%	10 - 95% RH
Cooling	-	Convection or forced air (30CFM or 3.1m/s). Internal fan is temperature controlled
Withstand Voltage (1)	-	Input to Ground 1.5kVAC, Input to Output 4kVAC(1), Output to Ground 500VAC for 1 min.
Isolation Resistance	-	>20M at 25°C & 70%RH, Output to Ground 500VDC
Vibration (non operating)	-	19.6m/s ² (10~55Hz:2G Constant, X,Y,Z 60min each.)
Shock	-	< 196.1 m/s ² (20G)
Safety Agency Approvals	-	Medical Version: IEC/UL/CSA/EN60601-1, ANSI/AAMI/ES60601-1, Industrial Version: IEC/UL/CSA/EN62368-1, 60950-1, CE Mark
Conducted & Radiated EMI	-	Medical Version: EN55011-B, Industrial: EN55032, FCC Class B
Immunity	-	Medical Version: EN60601-1-2, Industrial: EN55032
MTBF	-	>68,695 (MIL-217F-HDBK)
Weight (Typ)	g	860g (U channel), 980g (End Fan)
Size (LxWxH)	mm	U Channel: 203.2 x 119.4 x 38.4mm, End Fan (S): 228.6 x 119.4 x 41.4mm, Top Fan (T): 203.2 x 119.4 x 72.4mm
Size (LxWxH)	in	U Channel: 8 x 4.7 x 1.51", End Fan (S): 9 x 4.7 x 1.63", Top Fan (T): 8 x 4.7 x 2.85"
Warranty	yrs	Two Years

(1) Industrial version (I suffix): 3kVAC

Medical version: Input to ground (1xMOPP), Input to output 4kVAC (2xMOPP)

