

Evaluating the **ADuM5028**, Low Emission, Isolated, DC-to-DC Converter

FEATURES

- Signal and power isolated **ADuM5028** with *isoPower* integrated isolated dc-to-dc converter
- 2-layer PCB with low radiated emissions; passes EN55022 Class B (certification available)
- On-board LDO for 6 V to 9 V supply, providing 5 V to the **ADuM5028** V_{DDP} pin
- 5 V input and 5 V or 3.3 V output operation
- Screw terminal connectors for the following
 - 6 V to 9 V LDO power supply
 - 5 V direct power supply
 - Off board PDIS control
 - Isolated output supply

EVALUATION KIT CONTENTS

- EVAL-ADuM5028EBZ evaluation board
- ADuM5028-5BRIZ**

DOCUMENTS NEEDED

- ADuM5028** data sheet

GENERAL DESCRIPTION

The EVAL-ADuM5028EBZ allows the user to evaluate the **ADuM5028** isolated power solution. The **ADuM5028** eliminates the need to design and build an isolated dc-to-dc converter in 60 mA applications. The *iCoupler*® chip scale transformer technology is used for the inductive component of the dc-to-dc converter. The result is a small form factor, isolated solution.

Based on the Analog Devices, Inc., *iCoupler* technology, the **ADuM5028** dc-to-dc converter provides regulated, isolated power that is well below CISPR22 Class B limits when at full load on a 2-layer printed circuit board (PCB) with ferrites. Available supply voltages and the associated output current levels are shown in Table 1.

Full specifications of the **ADuM5028** can be found in the **ADuM5028** data sheets available from Analog Devices, and must be consulted in conjunction with this user guide when using the evaluation board.

EVALUATION BOARD PHOTOGRAPH



Figure 1.

Table 1. **ADuM5028** Output Current Levels

Model	Isolation Voltage (kV rms)	V_{IN} (V)	V_{OUT} (V)	85°C I_{OUT} (mA)	105°C I_{OUT} (mA)	125°C I_{OUT} (mA)
ADuM5028-5BRIZ	3	5	5	60	40	20
ADuM5028-5BRIZ	3	5	3.3	60	40	20

TABLE OF CONTENTS

Features	1	PCB Layout Recommendations	3
Evaluation Kit Contents.....	1	EN55022 Radiated Emissions Test Results	4
Documents Needed.....	1	Evaluation Board Schematic and Artwork.....	5
Evaluation Board Photograph.....	1	Ordering Information	7
General Description	1	Bill of Materials.....	7
Revision History	2	Related Links.....	7
Evaluation Board Hardware.....	3		
Using the Evaluation Board	3		

REVISION HISTORY

7/2018—Rev. 0 to Rev. A

Changed ADuM5028-5BRWZ to
ADuM5028-5BRIZ..... Throughout

5/2018—Revision 0: Initial Version

EVALUATION BOARD HARDWARE USING THE EVALUATION BOARD

Figure 1 shows the EVAL-ADuM5028EBZ evaluation board. The ADuM5028 sample device can be powered directly or through the on-board low dropout regulator (LDO). Either power scheme can be used without modification to the EVAL-ADuM5028EBZ evaluation board. The LDO input supply, Pin 1 of Screw Terminal P1 (marked VREG on the silkscreen), requires a power supply voltage of 6 V to 9 V. The LDO generates the required 5 V to the ADuM5028 V_{DDP} pin. The complete board can be powered by a 9 V battery (when testing for electromagnetic compatibility (EMC), for example). Alternatively, the ADuM5028 device can be powered directly with a 5 V supply through Pin 2 of Screw Terminal P1 (marked VDDP on the silkscreen). In both schemes, the power supply return connects to Pin 3 of Screw Terminal P1 (marked GND1 on the silkscreen). The jumper on JP1 must be installed to short JP1 Pin 3 and JP1 Pin4 to pull the PDIS pin low and enable the ADuM5028 when no external control signal is used. Installing the jumper on JP1 to short JP1 Pin1 and JP1 Pin 2 pulls the PDIS input pin high, which disables the ADuM5028 device. The V_{ISO} output voltage is set to 5.0 V by installing a 0 Ω resistor in the R2 pull-up position, or the V_{ISO} output voltage is set to 3.3 V by installing a 0 Ω resistor in the R3 pull-down position.

PCB LAYOUT RECOMENDATIONS

The ADuM5028 uses a 180 MHz oscillator frequency to pass power through its chip scale transformers. Bypass capacitors are required for several operating frequencies. Noise suppression requires low inductance and a high frequency capacitor. Ripple suppression and proper regulation require a large value capacitor. These capacitors are most effective when connected directly adjacent to the V_{DDP} pin and the GND_1 pin, and directly adjacent to the V_{ISO} pin and the GND_{ISO} pin. To suppress noise and reduce ripple, a parallel combination of at least two capacitors is required. The recommended capacitor values for V_{DDP} are 0.1 μF and 10 μF . The smaller capacitor must have a low equivalent series resistance (ESR). Use of a ceramic capacitor is advised. The total lead length between the ends of the low ESR capacitor and the input power supply pin must not exceed 2 mm.

To reduce the level of electromagnetic radiation, increase the impedance to high frequency currents between the V_{ISO} pin and the GND_{ISO} pin and the PCB trace connections. Using this method of emissions suppression controls the radiating signal at its source by placing surface-mount ferrite beads in series with the V_{ISO} pin and GND_{ISO} pin (see Figure 5). The impedance of the ferrite bead is approximately 1.8 k Ω between the 100 MHz and 1 GHz frequency range. This impedance value reduces the emissions at the 180 MHz primary switching frequency and the 360 MHz secondary side rectifying frequency and harmonics. See Table 2 for examples of appropriate surface-mount ferrite beads.

Table 2. Surface-Mount Ferrite Beads

Manufacturer	Part No.
Taiyo Yuden	BKH1005LM182-T
Murata Electronics	BLM15HD182SN1

To pass EN55022 Class B on a 2-layer PCB, the following layout guidelines for ADuM5028 are recommended (see Figure 2 and Figure 5):

- Place ferrite beads between the PCB trace or plane connections and V_{ISO} (Pin 6) and GND_{ISO} (Pin 5).
- Do not connect the V_{ISO} load to a PCB power plane (see Figure 5). Connect the V_{ISO} load using a PCB trace.
- Ensure V_{ISO} (Pin 6) is connected first through the E2 ferrite before connecting it to the V_{ISO} load (see Figure 2).
- Ensure GND_{ISO} (Pin 5) is connected by a trace to the GND_{ISO} pins (Pin 7) on the inside (device side) of the C4 100 nF capacitor.
- Ensure the C4 capacitor is connected between V_{ISO} (Pin 6) and GND_{ISO} (Pin 5) on the device side of the E3 and E2 ferrite beads.
- Ensure there is a keep out area in the PCB layout around the E2 and E3 ferrites, as shown in Figure 2 (no PCB planes under or alongside E2 and E3).




Figure 2. Layout Guidelines for EVAL-ADuM5028EBZ

- Locate the power delivery circuit in close proximity to the ADuM5028 device to ensure the V_{DDP} trace is as short as possible. The EVAL-ADuM5028EBZ PCB has a power delivery circuit located on the PCB with a short trace from the ADP7104ACPZ regulator output (U1) to V_{DDP} (Pin 3). This layout example minimizes the loop area in which high frequency current can flow. An increase in the loop area results in an increase in the emissions levels.
- To improve emissions, use Murata BLM18HE152SN1D ferrites (0603 size, SMD) for E1, E4, and E5, which are 1500 Ω at 100 MHz to 1 GHz. Other ferrites can be used for E1, E4, and E5; however, because of the input power requirements, they must be 0603 size ferrites.

EN55022 RADIATED EMISSIONS TEST RESULTS

The EVAL-ADuM5028EBZ evaluation board is tested and certified to pass the EN55022 Class B standard. EN55022 certification documents for the EVAL-ADuM5028EBZ evaluation board are available upon request from Analog Devices. Table 3 provides a summary of the results. All EN55022 radiated emissions tests were performed with the PCB schematic and layout as shown in Figure 5 to Figure 7.

The EVAL-ADuM5028EBZ evaluation board is configured and tested with 5.0 V power supplied to the VDDP pin from the ADP7104ACPZ regulator output. The ADP7104ACPZ regulator input is supplied from a standard 9 V battery. The V_{ISO} load can be loaded with six 300 Ω , 0805 size, SMD resistors in parallel for a total load of 100 Ω or 50 mA load at 5 V. Measurements carried out according to the EN55022 Class B standard in a semianechoic chamber at 10 m from 30 MHz to 1 GHz are shown in Figure 3 and Figure 4. Figure 3 shows the results of the peak horizontal scan (the worst case), and Figure 4 shows the results of the peak vertical scan. Table 3 shows the tabulated quasi peak (QP) results. These results show that the ADuM5028 emissions at -4.2 dB margin are well below CISPR22 Class B limits when at 5 V output and 50 mA load on a 2-layer PCB with the use of ferrites.




Figure 3. Horizontal Scan from 30 MHz to 1 GHz with 50 mA, 5 V Output




Figure 4. Vertical Scan from 30 MHz to 1 GHz with 50 mA, 5 V Output

Table 3. ADuM5028 Test Results (QP Measurements)

Frequency (MHz)	QP Level dB ($\mu\text{V}/\text{m}$)	Limit EN55022 Class B dB ($\mu\text{V}/\text{m}$)	QP Margin from Limit EN55022 Class B dB ($\mu\text{V}/\text{m}$)	Antenna Position	Antenna Height (m)	5 V In, 5 V Out Output Current (mA)	Pass/Fail
341.34	29.2	37	-7.8	Horizontal	3.0	50	Pass
383.32	27.2	37	-9.8	Horizontal	2.5	50	Pass
452.33	32.8	37	-4.2	Horizontal	2.5	50	Pass
380	23.0	37	-14.0	Vertical	2.0	50	Pass

EVALUATION BOARD SCHEMATIC AND ARTWORK

500-56991




Figure 5. EVAL-ADuM5028EBZ Evaluation Board Schematic




Figure 6. EVAL-ADuM5028EBZ Evaluation Board Top Layer and Silkscreen




Figure 7. EVAL-ADuM5028EBZ Evaluation Board Bottom Layer and Silkscreen

ORDERING INFORMATION

BILL OF MATERIALS

Table 4.

Reference Designator	Description	Supplier	Part No.
U2	ADuM5028 low emission isolated, dc-to-dc converter	Analog Devices	ADuM5028-5BRIZ
U1	ADP7104 20 V, 500 mA, low noise, complimentary metal oxide semiconductor (CMOS) LDO	Analog Devices	ADP7104ACPZ
C1, C2, C5, C6, C8	Capacitors, X7R, 10 μ F, 0805	Würth Elektronik	885012207026
C3, C4, C7	Capacitors, X7R, 0.1 μ F, 0603	Würth Elektronik	885012206046
E1, E4, E5	Ferrite beads, 1500 Ω , 0603	Murata	BLM18HE152SN1D
E2, E3	Ferrite beads, 1.8 k Ω at 100 MHz, 0402	Taiyo Yuden	BKH1005LM182-T
JP1	100 mil (2.54 mm) connector PCB header	Würth Elektronik	61300421121
Not applicable	100 mil (2.54 mm) jumper	FCI	65474-001LF
P1	Connector, PCB, terminal block, 5.0 mm pitch, 16-26 AWG	Würth Elektronik	691213710003
P3, P6	Connectors, PCB, terminal blocks, horizontal cable entry, 5 mm pitch	Würth Elektronik	691 213 710 002
R10	Resistor, 22.1 k Ω , 0603	Panasonic	ERJ-3EKF2212V
R8, R11	Resistors, 13.0 k Ω , 0603	Panasonic	ERJ-3EKF1302V
R13	Resistor, 100 k Ω , 0603	Panasonic	ERJ-3EKF1003V
R3	Resistor, 0 Ω , 0603	Vishay	CRCW06030000Z0EA
R9	Resistor, 18.2 k Ω , 0603	Panasonic	ERJ-3EKF1822V
TP1 to TP6	Connector PCB test points	Vero Technology	20-2137
P2, P5	Connector PCB headers, 2.54 mm, 3 position vertical (not installed)	MOLEX	22-03-2031
R12	Resistor, 0 Ω , 0603 (not installed)	Panasonic	ERJ-3GEY0R00V
R2	Resistor, 0 Ω , 0603 (not installed)	Vishay	CRCW06030000Z0EA
R1, R4 to R7, R14	Resistors, 300 Ω , 0805 (not installed)	Panasonic	ERJ-6ENF3000V

RELATED LINKS

Resource	Description
ADuM5028	Low Emission, Isolated, DC-to-DC Converter
AN-1349	PCB Implementation Guidelines to Minimize Radiated Emissions on the ADM2582E/ADM2587E RS-485/RS-422 Transceivers
AN-0971	Recommendations for Control of Radiated Emissions with <i>isoPower</i> ® Devices

NOTES

**ESD Caution**

ESD (electrostatic discharge) sensitive device. Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

Legal Terms and Conditions

By using the evaluation board discussed herein (together with any tools, components documentation or support materials, the "Evaluation Board"), you are agreeing to be bound by the terms and conditions set forth below ("Agreement") unless you have purchased the Evaluation Board, in which case the Analog Devices Standard Terms and Conditions of Sale shall govern. Do not use the Evaluation Board until you have read and agreed to the Agreement. Your use of the Evaluation Board shall signify your acceptance of the Agreement. This Agreement is made by and between you ("Customer") and Analog Devices, Inc. ("ADI"), with its principal place of business at One Technology Way, Norwood, MA 02062, USA. Subject to the terms and conditions of the Agreement, ADI hereby grants to Customer a free, limited, personal, temporary, non-exclusive, non-sublicensable, non-transferable license to use the Evaluation Board FOR EVALUATION PURPOSES ONLY. Customer understands and agrees that the Evaluation Board is provided for the sole and exclusive purpose referenced above, and agrees not to use the Evaluation Board for any other purpose. Furthermore, the license granted is expressly made subject to the following additional limitations: Customer shall not (i) rent, lease, display, sell, transfer, assign, sublicense, or distribute the Evaluation Board; and (ii) permit any Third Party to access the Evaluation Board. As used herein, the term "Third Party" includes any entity other than ADI, Customer, their employees, affiliates and in-house consultants. The Evaluation Board is NOT sold to Customer; all rights not expressly granted herein, including ownership of the Evaluation Board, are reserved by ADI. CONFIDENTIALITY. This Agreement and the Evaluation Board shall all be considered the confidential and proprietary information of ADI. Customer may not disclose or transfer any portion of the Evaluation Board to any other party for any reason. Upon discontinuation of use of the Evaluation Board or termination of this Agreement, Customer agrees to promptly return the Evaluation Board to ADI. ADDITIONAL RESTRICTIONS. Customer may not disassemble, decompile or reverse engineer chips on the Evaluation Board. Customer shall inform ADI of any occurred damages or any modifications or alterations it makes to the Evaluation Board, including but not limited to soldering or any other activity that affects the material content of the Evaluation Board. Modifications to the Evaluation Board must comply with applicable law, including but not limited to the RoHS Directive. TERMINATION. ADI may terminate this Agreement at any time upon giving written notice to Customer. Customer agrees to return to ADI the Evaluation Board at that time. LIMITATION OF LIABILITY. THE EVALUATION BOARD PROVIDED HEREUNDER IS PROVIDED "AS IS" AND ADI MAKES NO WARRANTIES OR REPRESENTATIONS OF ANY KIND WITH RESPECT TO IT. ADI SPECIFICALLY DISCLAIMS ANY REPRESENTATIONS, ENDORSEMENTS, GUARANTEES, OR WARRANTIES, EXPRESS OR IMPLIED, RELATED TO THE EVALUATION BOARD INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, TITLE, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF INTELLECTUAL PROPERTY RIGHTS. IN NO EVENT WILL ADI AND ITS LICENSORS BE LIABLE FOR ANY INCIDENTAL, SPECIAL, INDIRECT, OR CONSEQUENTIAL DAMAGES RESULTING FROM CUSTOMER'S POSSESSION OR USE OF THE EVALUATION BOARD, INCLUDING BUT NOT LIMITED TO LOST PROFITS, DELAY COSTS, LABOR COSTS OR LOSS OF GOODWILL. ADI'S TOTAL LIABILITY FROM ANY AND ALL CAUSES SHALL BE LIMITED TO THE AMOUNT OF ONE HUNDRED US DOLLARS (\$100.00). EXPORT. Customer agrees that it will not directly or indirectly export the Evaluation Board to another country, and that it will comply with all applicable United States federal laws and regulations relating to exports. GOVERNING LAW. This Agreement shall be governed by and construed in accordance with the substantive laws of the Commonwealth of Massachusetts (excluding conflict of law rules). Any legal action regarding this Agreement will be heard in the state or federal courts having jurisdiction in Suffolk County, Massachusetts, and Customer hereby submits to the personal jurisdiction and venue of such courts. The United Nations Convention on Contracts for the International Sale of Goods shall not apply to this Agreement and is expressly disclaimed.