

SIMATIC IoT2000, input module sink/source, 10x DI, ARDUINO Shield for SIMATIC IoT2020 and IoT2040



Installation type/mounting	
Mounting	On Arduino interface
Design	Plug-in card
Supply voltage	
Type of supply voltage	24 V DC
Digital inputs	
Number of digital inputs	10
Input voltage	<ul style="list-style-type: none"> • for signal "0" • for signal "1"
	< 5 V DC
	> 12 V DC
Input current	<ul style="list-style-type: none"> • for signal "0", max. (permissible quiescent current) • for signal "1", typ.
	0.9 mA
	2.1 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— at "0" to "1", max.	1.5 ms
— at "1" to "0", max.	1.5 ms
Digital outputs	
Type of digital output	without
EMC	
Interference immunity against discharge of static electricity	<ul style="list-style-type: none"> • Interference immunity against discharge of static electricity
	± 6 kV contact discharge at the front in accordance with IEC 61000-4-2; ±4 kV, housing contact discharge at the back in accordance with IEC 61000-4-2; ± 8 kV air discharge in accordance with IEC 61000-4-2
Interference immunity to cable-borne interference	<ul style="list-style-type: none"> • Interference immunity on signal cables < 30m
	±1 kV acc. to IEC 61000-4-4, Burst
Emission of conducted and non-conducted interference	<ul style="list-style-type: none"> • Interference emission via line/AC current cables
	10 V/m for 80 - 2 000 MHz, 80 % AM acc. to IEC 61000-4-3; 3 V/m for 2 - 2.7 GHz, 80 % AM acc. to IEC 61000-4-3
Compliance with line harmonic distortion limits	<ul style="list-style-type: none"> • Compliance with line harmonic distortion acc. to IEC 61000-3-2, IEC 61000-3-3
	No
Degree and class of protection	
IP (at the front)	20
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes
FCC	Yes

EMC	CE (industry)
Ambient conditions	
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	70 °C
Mechanics/material	
Enclosure material (front)	plastic
• Plastic	Yes
• Aluminum	No
• Stainless steel	No
• Glass	No
Dimensions	
Width	75 mm
Height	57 mm
Depth	32 mm
last modified:	10/30/2021 