Refer to pages 48-51 for Fuse Clip Layout and Mounting Details 1AG, 3AG, 7AG, 8AG

THRU HOLE MOUNT TYPES

WITH SNAP-IN PC LEGS



MATERIAL: .020 (.51) Brass, Tin Plate **UL Current Rating: 15 Amps**

.280 [7.1] .430 [10.9] .175 [4.5] [5.8] .060 [1.50] .325 [8.5] 1 .098 [2.5] DIA.

Mounting Detail

.300 [7.6] O DIA. S


WITH SNAP-IN PC LEGS



MATERIAL:

.020 (.51) Brass, Tin Plate **UL Current Rating: 15 Amps**

| CAT. NO. | A | В | |
|----------|------------|------------|--|
| 3515 | .060 (1.5) | .060 (1.5) | |
| 3515P | .060 (1.5) | .093 (2.4) | |
| 3516P | .060 (1.5) | .120 (3.0) | |




With or Without Orientation Legs

CAT. NO. 3513

WITH STRAIGHT PC LEGS



MATERIAL: .020 (.51) Brass, Tin Plate **UL Current Rating:** 15 Amps



.156 [4.0] —

.280 [7.1]

.453 [11.5]

[7.9]

.135 [3.5] DIA.

Mounting Detail




WITH STRAIGHT PC LEGS



MATERIAL: .020 (.51) Brass, Tin Plate **UL Current Rating:** 15 Amps

| CAT. NO. | Н | L | END STOPS |
|----------|-------------|------------|------------------|
| 3510 | .421 (10.7) | .140 (3.6) | NO* |
| 3529 | .421 (10.7) | .140 (3.6) | YES |
| 3511 | .430 (10.9) | .250 (6.4) | NO* |
| 3514 | .430 (10.9) | .250 (6.4) | YES |



Mounting Detail .300 [7.6] O

CAT. NO. 3530

MATERIAL:

CAT. NO.

3535

.020 (.51) Brass, Nickel Plate

UL Current Rating: 15 Amps

Α

В Flat .656 (16.7) 45° .562 (14.3)


WITH SOLDER LUG

1AG, 3AG, 7AG, 8AG RIVET & SURFACE MOUNT TYPES



MATERIAL:

.020 (.51) Brass, Nickel Plate **UL Current Rating:** 15 Amps





CAT. NO. 3531 (Without End Stops)*

47

WITHOUT LUG


.312 [7.9]



MATERIAL:

.020 (.51) Brass, Nickel Plate **UL Current Rating:** 15 Amps

CAT. NO. 3570



WITH OR WITHOUT END STOPS


LOW PROFILE



MATERIAL:

.020 (.51) Brass, Nickel Plate **UL Current Rating:** 15 Amps

| CAT. NO. | END STOPS |
|----------|-----------|
| 3532 | YES |
| 3567 | NO* |



*Fuse clips without end stops are not UL recognized