


LOC E	DIST B	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
	B1	REVISED PER ECO-11-005033	01APR11	RK	HMR

NOTES:

- 1 PACK IN ACCORDANCE WITH AMP SPEC 107-3275
- 2 100 TRAY PACK IN ACCORDANCE WITH AMP SPEC 107-3275
- 3 Au PLATING
- 4 ELECTRICAL CHARACTERISTICS  
 FREQUENCY RANGE: DC - 4 GHz  
 NOMINAL IMPEDANCE: 50 Ohm  
 INSULATION RESISTANCE: 1000 MOhm  
 WORKING VOLTAGE: 250 Volts RMS at Sea Level  
 DIELECTRIC WITHSTAND VOLTAGE: 750 Volts RMS Max  
 CONTACT RESISTANCE:  
 CENTRE CONTACT: 6.00 mOhm Max  
 OUTER CONTACT: 1.00 mOhm Max  
 VSWR @ 3GHz: 1.63:1  
 INSERTION LOSS dB @ x 1.5 GHz: 0.60 Max
- 5 MECHANICAL CHARACTERISTICS  
 COUPLING NUT RETENTION FORCE: N/A  
 CABLE RETENTION FORCE:  
 RG174A/U, 188A/U, 316/U, URM95: 85N Min  
 RG178B/U, 196A/U: 25N Min  
 CLAMP NUT RECOMMENDED TORQUE: 0.6N  
 DURABILITY: 500 Cycles Min
- 6 ENVIRONMENTAL CHARACTERISTICS  
 OPERATING TEMPERATURE: -65 to +165 DegC
- 7 FOR TECHNICAL DATA REFER TO YOUR LOCAL TE CONNECTIVITY SALES OFFICE
- 8 ALL DIMENSIONS ARE NOMINAL FOR REFERENCE ONLY UNLESS OTHERWISE STATED



QTY	QTY PER ASSY	MATERIAL	DESCRIPTION	ITEM
1	1	BRASS	CLAMP NUT	10
1	1	BRASS	WASHER	9
1	1	BRASS	SLEEVE	8
1	1	BRASS	CAP	7
1	1	BRASS	CHASSIS	6
1	1	BERYLLIUM COPPER	CONTACT	5
1	1	BRASS	BODY	4
1	1	BRASS	SHELL	3
1	1	PTFE	INSULATION	2
1	1	BERYLLIUM COPPER	SPRING	1
6--0	1--0			
QUANTITY PER ASSY		PARTS LIST		

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN J.SANDWELL 05JUN06	<b>STE</b> TE Connectivity	
DIMENSIONS: mm		CHK S.PARLOW 05JUN06		
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD F.WHEELER-KING 05JUN06	NAME SMB ELBOW PLUG SOLDER 50 OHM	
0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -		PRODUCT SPEC -	RG174A/U, 188A/U, 316/U, URM95, KX 3B, KX22A	
MATERIAL SEE TABLE		FINISH -	APPLICATION SPEC 411-3268	RESTRICTED TO -
		WEIGHT -	SIZE A3	CAGE CODE 00779
			DRAWING NO C-1478008	SCALE NTS
		CUSTOMER DRAWING	SHEET 1 OF 1	REV B1