



# **Product Description**

Security & Sound Cable, Plenum-CMP 4-18 AWG solid bare copper conductors with Flamarrest® insulation, Flamarrest® jacket with ripcord

## **Technical Specifications**

### **Product Overview**

Suitable Applications: Security System, Intercom/PA, Audio/Speaker, Power-Limited Cor						r-Limited Controls	
Constructi	on Deta	ils					
Conductor							
Element	No. of Ele	ements	Size	Stranding	Material		
Conductor(s)	4	18	AWG	Solid	BC - Bare Coppe	er	
nsulation							
Element	М	aterial	Nor	m. Thickne	ss Nom. Insula	tion Diameter	Color Code
Conductor(s)	PVC - Pol	lyvinyl Chlo	ride 0.0	1 in (0.25 m	nm) 0.0605 in (1.	54 mm)	Black, Red, White, Green
No Shield Duter Jacket Materi	ial	Nom. Th	icknoss	Nom. Dia	ameter Ripcord	0	
PVC - Polyvin					Yes		
· · · · · · · · · · · · · · · · · · ·	, ononde	0.010 111 (0	0.00 mm	, 0.171111	105		
			0.171 in	_			
Electricals	Characte	eristics				a	
Electrical C Electricals Nom. Conduc	Charactor	eristics Nom. Cap	acitance	Cond-to-C		x. Current	
Electrical C	Charactor	eristics	acitance	Cond-to-C		x. Current Conductor at 2	25°C
Electrical C Electricals Nom. Conduc 6.65 Ohm/100	Charactor	eristics Nom. Cap	acitance	Cond-to-C			25°C
Electrical C Electricals Nom. Conduc	Character ctor DCR Oft	eristics Nom. Cap	acitance	Cond-to-C			25°C
Electrical C Electricals Nom. Conduc 6.65 Ohm/100 Voltage UL Voltage R 300 V	character stor DCR Oft	Nom. Cap: 29 pF/ft (9:	acitance 5 pF/m)	Cond-to-C			25°C
Electrical C Electricals Nom. Conduc 6.65 Ohm/100 Voltage UL Voltage R 300 V Mechanica	character stor DCR Oft	Nom. Cap: 29 pF/ft (9:	acitance 5 pF/m)	Cond-to-C			25°C
Electrical C Electricals Nom. Conduc 6.65 Ohm/100 Voltage UL Voltage R 300 V Mechanica	character etor DCR Oft I Character ure Ope	Nom. Cap: 29 pF/ft (9:	acitance 5 pF/m)	Cond-to-C			25°C
Electrical C Electricals Nom. Conduc 6.65 Ohm/100 Voltage UL Voltage R 300 V Mechanica Temperature UL Temperatu	character etor DCR Oft I Character ure Ope	eristics Nom. Capa 29 pF/ft (95 cteristic	acitance 5 pF/m)	Cond-to-C			25°C
Electrical C Electricals Nom. Conduc 6.65 Ohm/100 Voltage UL Voltage R 300 V Mechanica Temperature UL Temperatu 75°C	character stor DCR off ating I Character 0°C T in. Insta	eristics Nom. Cape 29 pF/ft (95 cteristic cteristic orating io +75°C	acitance 5 pF/m) S	Cond-to-C			25°C

Bulk Cable Weight:	28.8 lbs/1000ft
--------------------	-----------------

**Standards and Compliance** 

Environmental Suitability:	Indoor
Flammability / Reaction to Fire:	NFPA 262 (UL910), FT6
NEC / UL Compliance:	Article 800, CMP
CEC / C(UL) Compliance:	CMP
European Directive Compliance:	EU CE Mark, EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Non-Plenum Number:	5322UE

#### History

Update and Revision:

Revision Number: 0.297 Revision Date: 05-05-2023

#### **Part Numbers**

#### Variants

Item #	Color	UPC
6322UE 877U100	) Natural	612825175964

© 2023 Belden, Inc

#### All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.