

NOTE:

MATERIAL

HOUSING:

PBT UL94V-0, BLACK

CONTACT:

BRASS

NUT:

BRASS

O-RING:

EPDM

FINISH

CONTACT:

GOLD PLATED
OVER 50U" NICKEL
NICKEL PLATED

ELECTRICAL

RATED CURRENT:

1.5A

RATED VOLTAGE:

30V

INSULATION RESISTANCE:

100 MΩhms MIN.

CONTACT RESISTANCE:

10 mΩhms MAX.

WATER PROOF:

IP67

ENVIRONMENT

OPERATION TEMPERATURE:

-40°C TO +85°C




860-012-113R00Y

3 = BRASS/NICKEL SHELL & NUT


S = STAINLESS STEEL SHELL & NUT

1 = GOLD FLASH

4 = 10u" GOLD



RECOMMEND P.C.B LAYOUT



RECOMMEND PANEL CUT-OUT

RoHS COMPLIANT

UNITS = mm

DO NOT SCALE FROM DRAWING



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:

M. SIGMON

DATE:

03-08-16

NorComp

SCALE:
NTSSHEET OF
1 1REV
6

DWG NO.

860-012-113R00Y