

Data sheet | Item number: 788-116

Jumper; for jumper slot; 6-way; insulated; light gray

www.wago.com/788-116



Color:

Data

Technical data

Main product function

Jumper

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

**Electrical data**

Rated current	18 A
---------------	------

Physical data

Width	79.2 mm / 3.118 inches
Height	21.5 mm / 0.846 inches
Depth	3.1 mm / 0.122 inches

Material Data

Color	light gray
Fire load	0.044 MJ
Weight	4.9 g

Commercial data

Product Group	6 (INTERFACE ELECTRONIC)
eCl@ss 10.0	27-14-11-40
eCl@ss 9.0	27-14-11-40
ETIM 8.0	EC002586
ETIM 7.0	EC002586
PU (SPU)	100 (25) pcs
Packaging type	box
Country of origin	DE
GTIN	4045454469382
Customs tariff number	85366990990

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Downloads**Documentation****Bid Text**

788-116 docx - Datei	2019 年2月20 日	docx 15.6 kB	Download
-------------------------	--------------	-----------------	----------

788-116 X81 - Datei	2019 年2月19 日	xml 2.5 kB	Download
------------------------	--------------	---------------	----------

Subject to changes. Please also observe the further product documentation!



Additional Information

Disposal and Recycling	V 1.1.0	pdf	Download
Electrical and electronic equipment, Batteries, Packaging	2022 年8月18 日	2.2 MB	

CAD/CAE-Data

CAE data

EPLAN Data Portal 788-116	URL	Download
WSCAD Universe 788-116	URL	Download
ZUKEN Portal 788-116	URL	Download

CAD data

2D/3D Models 788-116	URL	Download
----------------------	-----	----------

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 788-116	URL	Download
Jumper; for jumper slot; 6-way; insulated; light gray		

Installation Notes

Subject to changes. Please also observe the further product documentation!