

60Watts Single Output





Features:

- Universal AC input/ Full range
- Wide Operating Ambient Temperature (-25°C~70°C)
- High Efficiency, low power consumption
- Output Protections: OLP/OVP/SCP
- All using 105°C long life electrolytic capacitors.
- 100% full load burn-in test





Model	QPS-60-5	QPS-60-12	QPS-60-15	QPS-60-24	QPS-60-48
Output Characteristics					
DC Output	5V	12V	15V	24V	48V
Rated Current	8A	4.5A	3.6A	2.5A	1.25A
Current Range	0~8A	0~4.5A	0~3.6A	0~2.5A	0~1.25A
Ripple and Noise	0~70°C -25~0°C	<50mV <200mV	<120mV <300mV	<120mV <300mV	<240mV <360mV
Voltage ADJ. Range	4.5~5.5V	11.2~13.4V	13.8~16.5V	22.2~27.9V	45.0~53.2V
Voltage Accuracy	±3.0%				
Line Regulation	±0.5%				
Load Regulation	±2.0%				
Set-up Time	≤1.0s (230VAC input, full load)				
Hold-up Time	≥20ms (230VAC input, full load)				
Temperature Coefficient	±0.03%/°C				
Overshoot and Undershoot	<5.0%				
Input Characteristics					
Voltage Range	90VAC~264VAC, 127VDC~370VDC				
Frequency Range	47Hz-63Hz				
Efficiency	115VAC Input (Typical)	79%	83%	84%	87%
	230VAC Input	82%	85%	85%	87%
AC Current (max)	<1.5A				
Inrush Current (Typical)	30A@115VAC Cold start 60A@230VAC Cold start				
Leakage Current	<0.25mA				
Protection					
Over Load (OLP)	105%~180% of rated output current, hiccup mode, auto recover				
Over Voltage (OVP)	110%~150% of rated output voltage, constant voltage				
Short Circuit (SCP)	Long-term mode, auto recovery				
Environmental Characteristics					
Operating Amb. Temp. & Hum	-25°C~70°C; 20%~90% RH Non-Condensing				
Storage Temp. & Hum	-40°C~85°C: 10%-95% RH Non-Condensing				
Safety Standards	UL60950-1; EN60950-1: 2006				
Withstand Voltage	Primary-Secondary: 3.0KVAC;≤10mA.				
Isolation Resistance	≥100M ohms				
EMI Conduction & Radiation	Compliance to EN55022(CISPR22) Class B				
Harmonic Current	Compliance to EN61000-3-2, -3				
EMS Immunity	Compliance to EN61000-4-2, 3, 4, 5, 6, 8, 11; ENV50204, light industry level, criteria A				
General Characteristics					
MTBF (MIL-HDBK-217F)	More than 200,000Hrs (25°C, Full load)				
Dimension (LxWxH)	101.6x50.8x30mm				
Packing	60PCS/CTN. G.W: 12kgs				
Cooling Method	Cooling by free air convection				

MECHANICAL SPECIFICATIONS



ITEM	CONNECTOR	MATING HOUSING	TERMINAL
AC IN (CON1)	LANDWIN 3961P0300T (CENTER PIN REMOVED)	LANDWIN 3960S OR JST VHR	LANDWIN 3963T011R OR JST SVH-21T-P1.1
DC OUT (CON2)	LANDWIN 3961P0400T	OR MOLEX 51144	OR MOLEX 50539

DERATING CURVE



UNIT: mm