



- THIS PLUG IS DESIGNED TO CONFORM TO THE LATEST ISSUE OF MIL-C-24308
 - MAX WIRE INSUL. TO BE USED WITH THIS PLUG IS .054 DIA.
 - METAL RETENTION CLIPS ARE INCLUDED IN INSERTS
 - PACKAGE MARKED M 24308/4-333F
 - THIS PLUG WILL ACCEPT SIZE 22 PIN CONTACT M 24308/13 OR AMP # 204370
- AMP PART NO. MARKED ON CONNECTOR REPRESENTS KIT NUMBER WITH CONTACTS
 UL/CSA DESIGNATION MARKED IN THIS AREA.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN C.C.THOMAS 12-4-87	TE Connectivity
DIMENSIONS: INCHES		CHK F.C.BALLEW III 1-25-88	
DIMENSIONS: INCHES 0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± .005 4 PLC ± - ANGLES ± 0'30"		APVD F.C.BALLEW III 1-25-88 PRODUCT SPEC APPLICATION SPEC WEIGHT CUSTOMER DRAWING	NAME AMPLIMITE PLUG FOR PIN CONTACTS HI-DENSITY D CONNECTOR SIZE 5, 78 POSN., SERIES 90 WITH FLOAT BUSHINGS
MATERIAL SEE CALLOUTS		FINISH SEE CALLOUTS	SIZE A1 CAGE CODE 00779 DRAWING NO 204533 SCALE 4:1 SHEET 1 OF 1 REV S