

CA-16P1NC22S00 - Device connector front mounting



1619907

<https://www.phoenixcontact.com/us/products/1619907>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Device connector front mounting, series: CA, straight, shielded: yes, for standard and SPEEDCON interlock, No. of pos.: 16, Direction of rotation: Standard, contact connection type: Pin, Solder-in connection, Flat gasket, 4x Ø 3.2, flange dimensions: 25 mm x 25 mm, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1243885

Your advantages

- Safe use in the field, thanks to high degree of protection
- Consistent EMC protection for reliable transmission of signals
- Easy device integration: solder-in contacts available in different lengths

Commercial data

Item number	1619907
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB33
Product key	ABRAEL
GTIN	4046356820608
Weight per piece (including packing)	31.3 g
Weight per piece (excluding packing)	31.3 g
Customs tariff number	85366990
Country of origin	DE

1619907

<https://www.phoenixcontact.com/us/products/1619907>

Technical data

Product properties

Product type	Circular connectors (device side)
--------------	-----------------------------------

Dimensions

Length of the solder pin	17.5 mm
	17.5 mm

Connector

Insulating body

Coding	N
Insulation body material	PBT
Contact material	CuZn
Contact surface material	Ni/Au
Connection method	Solder-in connection
Contact switching type	Pin
Application	Signal
Number of positions	16
Direction of rotation	Standard
Connection profile	16
Contact diameter	1 mm
Power contacts	
Rated current	8 A
Rated surge voltage	1.5 kV
Overvoltage category	III
Degree of pollution	3

Housing

Housing material	GD-Zn
Flange dimensions	25 mm x 25 mm
Type of locking	for standard and SPEEDCON interlock
Pg screw connection	none
Degree of protection (plugged in)	IP67
Thread type	M23

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

CA-16P1NC22S00 - Device connector front mounting




1619907

<https://www.phoenixcontact.com/us/products/1619907>

Drawings

Schematic diagram




CA-16P1NC22S00 - Device connector front mounting



1619907

<https://www.phoenixcontact.com/us/products/1619907>

Drilling plan/solder pad geometry



16-pos.

CA-16P1NC22S00 - Device connector front mounting





1619907

<https://www.phoenixcontact.com/us/products/1619907>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1619907>

 cUL Recognized Approval ID: E335019-20141210				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	48 V	5 A	- 18	-

 UL Recognized Approval ID: E335019-20141210				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	48 V	8 A	- 18	-

cULus Recognized				
-------------------------	--	--	--	--

CA-16P1NC22S00 - Device connector front mounting



1619907

<https://www.phoenixcontact.com/us/products/1619907>

Classifications

ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116

ETIM

ETIM 8.0	EC002635
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

CA-16P1NC22S00 - Device connector front mounting



1619907

<https://www.phoenixcontact.com/us/products/1619907>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

CA-16P1NC22S00 - Device connector front mounting



1619907

<https://www.phoenixcontact.com/us/products/1619907>

Accessories

SF-Z0019 - Protective cap

1607449

<https://www.phoenixcontact.com/us/products/1607449>



Plastic protection cap, with eye, IP40 for connectors with M23 external thread, RF, SF series

RC-Z2059 - Protective cap

1604225

<https://www.phoenixcontact.com/us/products/1604225>



Plastic protection cap for connectors with M23 external thread

CA-16P1NC22S00 - Device connector front mounting



1619907

<https://www.phoenixcontact.com/us/products/1619907>

RC-Z2469 - Protective cap

1611797

<https://www.phoenixcontact.com/us/products/1611797>



Plastic protection cap, antistatic, for RF, SF, CA, RC series connectors, with M23 external thread

RC-Z2104 - Metal protective cap

1604260

<https://www.phoenixcontact.com/us/products/1604260>



Metal protective cap, M23, degree of protection: IP67, series: RC, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1241739

CA-16P1NC22S00 - Device connector front mounting



1619907

<https://www.phoenixcontact.com/us/products/1619907>

RC-Z2068 - Metal protective cap

1604236

<https://www.phoenixcontact.com/us/products/1604236>

Metal protective cap, M23, degree of protection: IP67, series: RC, Alternative product in accordance with RoHS II without Exemption 6c (Pb <0.1%) item no.: 1241735



CA-Z0120 - Color-coding

1620704

<https://www.phoenixcontact.com/us/products/1620704>

Color-coding, color: green



CA-16P1NC22S00 - Device connector front mounting



1619907

<https://www.phoenixcontact.com/us/products/1619907>

CA-Z0121 - Color-coding

1620705

<https://www.phoenixcontact.com/us/products/1620705>

Color-coding, color: orange



CA-Z0122 - Color-coding

1620706

<https://www.phoenixcontact.com/us/products/1620706>

Color-coding, color: black



CA-16P1NC22S00 - Device connector front mounting



1619907

<https://www.phoenixcontact.com/us/products/1619907>

CA-Z0001 - Contact removal tool

1620699

<https://www.phoenixcontact.com/us/products/1620699>



Unlocking tool for contact carriers for snapping in the M23 signal device connectors

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com