

Technical Data Sheet

2 Port USB Type-C To Serial Adapter with Per Port Rx / TX Status LED Matrix

Model Number: GM-FTDI2XC-LED

Rev 03.210319



2 Port USB-C to Serial adapter with RX/TX LED Indicators easily adds 2 standard serial ports to your desktop, laptop or other mobile device and fully supports Windows 10.

- RXD, TXD Status LED Array
- Easy Plug and Play installation
- USB interface: standard Type-C female
- Baud rates up to 921.600bps

Features

- Easy Plug and Play Installation
- RXD, TXD Status LED Array
- USB Interface: Standard Type-C female
- Automatic handshake support & Baud rates up to 921.600bps
- Dual 16 Byte hardware data buffer (up/down stream)

Product Information

- Model Number: GM-FTDI2XC-LED
- Packing List:
 -

Specifications
OVERVIEW

Product Type	Serial Cables
Electrical Protections	15KV ESD Protection
Mountable	
Material	
Compliance	N/A
LED indicators	Power, TX/RX
Requires Host to Function	

0

Serial Modes	RS232
RS232 Signals	DCD, RxD, TxD, DTR, GND, DSR, RTS, CTS, RI
RS422 Signals	
RS485 2-wire Signals	
RS485 4-wire Signals	

SERIAL SPECS

Maximum Data Rate	921.6 Kbps
Minimum Data Rate	300 baud/bps
Data Bits	
Parity	
Stop Bits	
Flow Control	
FIFO	

Specifications Cont.**ENVIRONMENTAL**

Operating Temperature	-40C ~ 85C
Operating Humidity	5% to 95% RH
Storage Temperature	-40C ~ 85C

PHYSICAL

Length	36 inches
Width	inches
Height	inches
Item Weight	0.281 lbs
Ship Weight	0.3875 lbs

OS SUPPORT

Supported Operating Systems	Linux, OSX 10, Windows 10, Windows 8, Windows 7, Windows Vista, Windows XP
-----------------------------	--

WARRANTY

Warranty Period	1 Year
-----------------	--------

PRODUCT URL

GM-FTDI2XC-LED Product Page	
-----------------------------	--