



TECHNICAL

LISTED: UL & CSA
 RATED SUPPLY VOLTAGE: 120VAC
 RATED CURRENT: UP TO 15 AMPS
 RESET TYPE: AUTO OR MANUAL
 OPERATING FREQUENCY: 60 Hz
 TYPE: CLASS A
 GROUND TRIP CURRENT: 5mA +/- 1mA
 OVERLOAD CURRENT: 90 AMPS, 0.45 PF
 INSULATION VOLTAGE: 1,500 VRMS - 1 MINUTE
 ENDURANCE OPERATIONS: 3000 OPERATIONS
 ENCLOSURE: NEMA 3R

MATERIAL NO.	ENGINEERING NO.	LENGTH "L"	POWER-UP
1301530267	15051-0M	2.5 FT	MANUAL

FUNCTIONAL SYMBOLS $\frac{F}{A} = 0$ $\frac{F}{C} = 0$ $\frac{F}{P} = 0$ DIVISIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC: NEW SALES DRAWING CREATED		
	DIMENSION UNITS	SCALE	EC NO: 679783		
	GENERAL TOLERANCES (UNLESS SPECIFIED)		DRWN: VBASUTHKARP 2021/10/05		
	ANGULAR TOL ± 0.5°		CHK'D: DNGUYEN62 2021/10/05		
4 PLACES ±		APPR: HKNEELAND 2021/10/11		PRODUCT CUSTOMER DRAWING	
3 PLACES ±		INITIAL REVISION:		DOCUMENT NUMBER	
2 PLACES ±		DRWN: HRUIZ01 2014/04/28		SD-130153-043	
1 PLACE ±		APPR: JFMURPHY 2014/08/07		PSD 001 B	
0 PLACES ±		THIRD ANGLE PROJECTION	DRAWING	SERIES	MATERIAL NUMBER
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			C-SIZE	130153	SEE TABLE
					CUSTOMER
					GENERAL MARKET
					SHEET NUMBER
					1 OF 1

DOCUMENT STATUS	P1	RELEASE DATE	2021/10/11 17:53:57
-----------------	----	--------------	---------------------