



ⓑ NOTES:

1. METAL SHELLS: STEEL; min. 315µm TIN over 40-80µm NICKEL
2. INSULATORS: PBT GF UL 94 V-0, BLACK
3. FRAME: STEEL; NICKEL PLATED
4. FLOAT MOUNTS: COPPER ALLOY; NICKEL PLATED
5. RIVETED INSERTS: COPPER ALLOY; min. 200µm TIN over 80µm NICKEL
6. COLLARS: COPPER ALLOY; min. 200µm TIN over 80µm NICKEL
7. CONNECTOR WILL BE SUPPLIED WITHOUT CONTACTS
8. CONNECTOR IS PART MARKED: DSS2XSXXB01X CONEC ABC

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND				tolerance		scale: 2:1
				dim. in mm		material: SEE NOTES
				date	name	title: D-SUB FEMALE 15pos. CRIMP STYLE with frame and float mount
				drawn 02.08.2005	Lehmenkühler	
				appd. 02.08.2005	Mickenbecker	
3 x c	Ä5047	16.01.14	Lehm.	d-old	dwg no:	DIN-A3
1 x b	Ä2880	04.12.07	Lehm.		16K1A1473	sh: 1
a	Original				part no:	DSS2XSXXB01X
rev.	description	date	name	CONEC ®		