

FDD8770/FDU8770 N-Channel PowerTrench® MOSFET

25V, 35A, 4.0mΩ



General Description





This N-Channel MOSFET has been designed specifically to improve the overall efficiency of DC/DC converters using either synchronous or conventional switching PWM controllers. It has been optimized for low gate charge, low $r_{DS(on)}$ and fast switching speed.

Features

- Max $r_{DS(on)}$ = 4.0mΩ at $V_{GS} = 10V$, $I_D = 35A$
- Max $r_{DS(on)}$ = 5.5mΩ at $V_{GS} = 4.5V$, $I_D = 35A$
- Low gate charge: $Q_{g(10)} = 52nC(Typ)$, $V_{GS} = 10V$
- Low gate resistance
- RoHS Compliant

Application

- Vcore DC-DC for Desktop Computers and Servers
- VRM for Intermediate Bus Architecture



MOSFET Maximum Ratings $T_C = 25^\circ C$ unless otherwise noted

| Symbol | Parameter | Ratings | Units |
|----------------|---|------------|------------|
| V_{DS} | Drain to Source Voltage | 25 | V |
| V_{GS} | Gate to Source Voltage | ± 20 | V |
| I_D | Drain Current -Continuous (Package Limited) | 35 | A |
| | -Continuous (Die Limited) | 210 | |
| | -Pulsed (Note 1) | 407 | |
| E_{AS} | Single Pulse Avalanche Energy (Note 2) | 113 | mJ |
| P_D | Power Dissipation | 115 | W |
| T_J, T_{STG} | Operating and Storage Temperature | -55 to 175 | $^\circ C$ |

Thermal Characteristics

| | | | |
|-----------------|--|-----|--------------|
| $R_{\theta JC}$ | Thermal Resistance, Junction to Case TO-252, TO-251 | 1.3 | $^\circ C/W$ |
| $R_{\theta JA}$ | Thermal Resistance, Junction to Ambient TO-252, TO-251 | 100 | $^\circ C/W$ |
| $R_{\theta JA}$ | Thermal Resistance, Junction to Ambient TO-252, 1in ² copper pad area | 52 | $^\circ C/W$ |

Package Marking and Ordering Information

| Device Marking | Device | Package | Reel Size | Tape Width | Quantity |
|----------------|--------------|----------|-----------|------------|------------|
| FDD8770 | FDD8770 | TO-252AA | 13" | 12mm | 2500 units |
| FDU8770 | FDU8770 | TO-251AA | N/A(Tube) | N/A | 75 units |
| FDU8770 | FDU8770_F071 | TO-251AA | N/A(Tube) | N/A | 75 units |

Electrical Characteristics $T_J = 25^\circ\text{C}$ unless otherwise noted

| Symbol | Parameter | Test Conditions | Min | Typ | Max | Units |
|--------|-----------|-----------------|-----|-----|-----|-------|
|--------|-----------|-----------------|-----|-----|-----|-------|

Off Characteristics

| | | | | | | |
|--------------------------------------|---|---|----|------|-----------|----------------------|
| B_{VDSS} | Drain to Source Breakdown Voltage | $I_D = 250\mu\text{A}, V_{GS} = 0\text{V}$ | 25 | | | V |
| $\frac{\Delta B_{VDSS}}{\Delta T_J}$ | Breakdown Voltage Temperature Coefficient | $I_D = 250\mu\text{A}$, referenced to 25°C | | 13.6 | | mV/ $^\circ\text{C}$ |
| I_{DSS} | Zero Gate Voltage Drain Current | $V_{DS} = 20\text{V}$, $V_{GS} = 0\text{V}$ $T_J = 150^\circ\text{C}$ | | | 1 250 | μA |
| I_{GSS} | Gate to Source Leakage Current | $V_{GS} = \pm 20\text{V}$ | | | ± 100 | nA |

On Characteristics

| | | | | | | |
|--|--|--|-----|------|-----|----------------------|
| $V_{GS(th)}$ | Gate to Source Threshold Voltage | $V_{GS} = V_{DS}, I_D = 250\mu\text{A}$ | 1.2 | 1.6 | 2.5 | V |
| $\frac{\Delta V_{GS(th)}}{\Delta T_J}$ | Gate to Source Threshold Voltage Temperature Coefficient | $I_D = 250\mu\text{A}$, referenced to 25°C | | -5.9 | | mV/ $^\circ\text{C}$ |
| $r_{DS(on)}$ | Drain to Source On Resistance | $V_{GS} = 10\text{V}, I_D = 35\text{A}$ | | 3.3 | 4.0 | m Ω |
| | | $V_{GS} = 4.5\text{V}, I_D = 35\text{A}$ | | 4.0 | 5.5 | |
| | | $V_{GS} = 10\text{V}, I_D = 35\text{A}$ $T_J = 175^\circ\text{C}$ | | 4.8 | 5.9 | |

Dynamic Characteristics

| | | | | | | |
|-----------|------------------------------|--|-------------------|------|------|----------|
| C_{iss} | Input Capacitance | $V_{DS} = 13\text{V}, V_{GS} = 0\text{V}$, $f = 1\text{MHz}$ | | 2795 | 3720 | pF |
| C_{oss} | Output Capacitance | | | 685 | 915 | pF |
| C_{rss} | Reverse Transfer Capacitance | | | 450 | 675 | pF |
| R_g | Gate Resistance | | $f = 1\text{MHz}$ | 1.5 | | Ω |

Switching Characteristics

| | | | | | | |
|--------------|-------------------------------|--|---|-----|----|----|
| $t_{d(on)}$ | Turn-On Delay Time | $V_{DD} = 13\text{V}, I_D = 35\text{A}$ $V_{GS} = 10\text{V}, R_{GS} = 5\Omega$ | | 10 | 20 | ns |
| t_r | Rise Time | | | 12 | 22 | ns |
| $t_{d(off)}$ | Turn-Off Delay Time | | | 49 | 78 | ns |
| t_f | Fall Time | | | 25 | 40 | ns |
| Q_g | Total Gate Charge | | $V_{GS} = 0\text{V to } 10\text{V}$ | | 52 | 73 |
| Q_g | Total Gate Charge | $V_{GS} = 0\text{V to } 5\text{V}$ | $V_{DD} = 13\text{V}$ $I_D = 35\text{A}$ $I_g = 1.0\text{mA}$ | 29 | 41 | nC |
| Q_{gs} | Gate to Source Gate Charge | | | 8.1 | | nC |
| Q_{gd} | Gate to Drain "Miller" Charge | | | 11 | | nC |

Drain-Source Diode Characteristics

| | | | | | | |
|----------|---------------------------------------|---|--|------|------|----|
| V_{SD} | Source to Drain Diode Forward Voltage | $V_{GS} = 0\text{V}, I_S = 35\text{A}$ | | 0.84 | 1.25 | V |
| | | $V_{GS} = 0\text{V}, I_S = 15\text{A}$ | | 0.79 | 1.0 | |
| t_{rr} | Reverse Recovery Time | $I_F = 35\text{A}, di/dt = 100\text{A}/\mu\text{s}$ | | 32 | 48 | ns |
| Q_{rr} | Reverse Recovery Charge | $I_F = 35\text{A}, di/dt = 100\text{A}/\mu\text{s}$ | | 25 | 38 | nC |

Notes:

- 1: Pulse time < 300 μs , Duty cycle = 2%.
- 2: Starting $T_J = 25^\circ\text{C}$, $L = 0.3\text{mH}$, $I_{AS} = 27.5\text{A}$, $V_{DD} = 23\text{V}$, $V_{GS} = 10\text{V}$.

Typical Characteristics $T_J = 25^\circ\text{C}$ unless otherwise noted




Figure 1. On Region Characteristics




Figure 2. Normalized On-Resistance vs Drain Current and Gate Voltage




Figure 3. Normalized On Resistance vs Junction Temperature




Figure 4. On-Resistance vs Gate to Source Voltage




Figure 5. Transfer Characteristics




Figure 6. Source to Drain Diode Forward Voltage vs Source Current

Typical Characteristics $T_J = 25^\circ\text{C}$ unless otherwise noted




Figure 7. Gate Charge Characteristics




Figure 8. Capacitance vs Drain to Source Voltage




Figure 9. Unclamped Inductive Switching Capability




Figure 10. Maximum Continuous Drain Current vs Case Temperature




Figure 11. Forward Bias Safe Operating Area





Figure 12. Single Pulse Maximum Power Dissipation

Typical Characteristics $T_J = 25^\circ\text{C}$ unless otherwise noted



TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

| | | | | |
|---|----------------------------------|----------------------------|----------------------------------|------------------------------|
| ACE ^x TM | FAST [®] | ISOPLANAR TM | PowerEdge TM | SuperFET TM |
| ActiveArray TM | FAST ^r TM | LittleFET TM | PowerSaver TM | SuperSOT TM -3 |
| Bottomless TM | FPS TM | MICROCOUPLER TM | PowerTrench [®] | SuperSOT TM -6 |
| Build it Now TM | FRFET TM | MicroFET TM | QFET [®] | SuperSOT TM -8 |
| CoolFET TM | GlobalOptoisolator TM | MicroPak TM | QS TM | SyncFET TM |
| CROSSVOLT TM | GTO TM | MICROWIRE TM | QT Optoelectronics TM | TCM TM |
| DOMET TM | HiSeC TM | MSX TM | Quiet Series TM | TinyLogic [®] |
| EcoSPARK TM | I ² C TM | MSXPro TM | RapidConfigure TM | TINYOPTO TM |
| E ² CMOS TM | <i>i-Lo</i> TM | OCX TM | RapidConnect TM | TruTranslation TM |
| EnSigna TM | ImpliedDisconnect TM | OCXPro TM | SerDes TM | UHC TM |
| FACT TM | IntelliMAX TM | OPTOLOGIC [®] | ScalarPump TM | UniFET TM |
| FACT Quiet Series TM | | OPTOPLANAR TM | SILENT SWITCHER [®] | UltraFET [®] |
| Across the board. Around the world. TM | | PACMAN TM | SMART START TM | VCX TM |
| The Power Franchise [®] | | POP TM | SPM TM | Wire TM |
| Programmable Active Droop TM | | Power247 TM | Stealth TM | |

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

| Datasheet Identification | Product Status | Definition |
|--------------------------|------------------------|---|
| Advance Information | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice. |
| Preliminary | First Production | This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| No Identification Needed | Full Production | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| Obsolete | Not In Production | This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only. |