


500688 – USB Standard “Type A” USB Plug to 4 Pin Single Row Housing

This cable is required for a USB interface with Bergquist controllers 500697 or 500698



PIN ASSIGNMENT

CON 1		CON 2
1	— RED (#24)	1
2	— WHITE (#28)	2
3	— GREEN (#28)	3 ∇
4	— BLACK (#24)	4
	SHELL	

NOTE:
(說明):

1. LENGTH OF CABLE-CUTTING: 1550±10mm ;
(1. CABLE 裁線長度: 1550±10mm ;)
2. THE LENGTH OF JACKET STRIPPIN OF CON1: 13±2mm ;
THE LENGTH OF JACKET STRIPPIN OF CON2: 25±2mm ;
(2. CABLE CON1端剝外被長度: 13±2mm;CON2端剝外被長度: 25±2mm;)
3. 100% INSULATIONSHORTMISS-WIRE TEST ;
(3. 100% 絕緣、短路、反線測試 ;)
4. TEST CONDITION: CT≤2Ω IS≥5MΩ .
(4. 測試條件 :CT≤2Ω IS≥5MΩ .)

F	TERMINAL	200PH-T (A2001-TP or EQUAL)	4PCS
E	HOUSING	200PH-04P (A2001H-4P or EQUAL)	1PCS
D	外模	PVC-45P 貝吉色	6.0g
C	CONN	USB A TYPE 公頭 白色膠芯 端子鍍一般金	1SET
B	H.S.TUBE	OD*L=5.0*10mm BLACK	1PCS
A	CABLE	UL 2725 #24*2C+#28*1P+AEB 貝吉色 L=1550mm	1PCS
NO	NAME	SPECIFICATION	QTY