PROPRIETARY INFORMATION:						REVISION						
PROPRIETARY OF GLOBTEK, INC. ANY USE OF THIS DRAWING, IN WHOLE OR PROHIBITED EXCEPT AS SPECIFIED IN					REV DESCRIPTION				DATE	APPROVED		
			PROHIBITED EXCEPT AS SPECIFIED IN WRITING BY GLOBT			A		INITIAL RELEASE		09/15/18	BS	
	ŀ	٩		2510 <u>+</u> :	50						•	
A _{GREEN}									GREEN GREEN BLACK	I	В	
	BLACK						5					
GENERAL SPECIFICATIONS: RATING: 10A / 250V				PACK BULK I								
CABLE TYPE TEMPERATUF CONDUCTOR CABLE JACKE OVERALL LEN CABLE OUTE END 'A' PLUG END 'B' :	RE RATING: COLORS: ET COLOR: NGTH (L): R DIAMETER:	60° C BLACK BLACK 2510 <u>+</u> 5 7.8 <u>+</u> 0. IEC 320		NOTES: 1. CORD, PLUG AND CONNECTOR MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).								
APPROVALS PLUG: UL, CSA or cUL APPROVALS CABLE: UL, CSA or cUL APPROVALS CONNECTOR: UL, CSA or cUL MUL, CSA or cUL APPROVALS CONNECTOR: UL, CSA or cUL MUL, CSA or cUL									Comments with Record			
								By N.Frost at 9:15 am, Sep 18, 201	8		000	
_				DASH NO.	PART NO F	REV.		DESCRIPTION			NOTES	
					TABULATION BLOCK							
				REV. SHEET		TOLERAI DECIMALS .xx +/- 0.1 .xxx +/005	+/- 1°		186 Veterans Dr. Tel. 201-784-1000			
				INIT.BY: BS	IIILLIMETERS ANGULAR .xx +/.0.3 +/.1' xxx +/.013 DWG TITLE: NORTH AMERICAN IEC JUMPER CORDSET							
Contents of this document are subject to change without prior notice	safety and performance of these product if unauthorized access an occurs. End user should consult t		mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written approval from the CEO of Globtek Inc.	DRAWN: NF		FSCN No.: G, CC	SIZE A				REV. A	
rtor notice ble UL _x CSA or EN Stand installation instruction.		as for proper	approval from the CEO of Oroblek life.		DATE: 09/15/18	SCALE: NO	DNE PA	RT NO: 7011438F2705(R)		SH	EET 1/1	