

Ethernet-based, Modular Media Converter Chassis

MediaConverter/4

B+B SMARTWORX

Powered by

ADVANTECH

www.advantech-bb.com



PRODUCT FEATURES

- Supports Fast Ethernet and Gigabit Ethernet
- Supports “Mc” modules
- Table-top
- 4-slot chassis
- Internal AC power
- Modular, hot-swappable architecture reduces operational costs associated with product installation, upgrades and maintenance

The unmanaged B+B SmartWorx' MediaConverter/4 enables you to install compact, horizontal modules that support speeds of 10/100Mbps, 100Mbps or Gigabit. The four-slot chassis is one of four chassis that can provide a low-cost solution for segments in a network that require a copper to fiber conversion.

The modules available from B+B SmartWorx for this chassis are the McLIM, McLIM-TP-TX/FX and McGigabit series.

The four slot-chassis has a reliable internal AC power supply. A country-specific power cord is shipped with each chassis.

ORDERING INFORMATION

MODEL NUMBER	DESCRIPTION
MediaConverter/4	
851-10904	4 Slot, AC Chassis

ACCESSORIES

895-39949 - Rackmount Shelf

All product specifications are subject to change without notice.
MediaConverter-4_4117ds

Ethernet-based, Modular Media Converter Chassis

MediaConverter/4



SPECIFICATIONS

TECHNICAL

4 slot chassis to house the following modules:
McLIM, McLIM 10/100, McGigabit

MECHANICAL

Dimensions 4.77H x 21.86W x 12.57D cm
(1.88H x 8.61W x 4.95D in.)

Shipping Weight 1.6 kg (3.5 lbs)

POWER

120/240 VAC, 50/60Hz, 1A/0.5A

ENVIRONMENTAL

Operating Temperature – DC Terminal Block 0° to +50° C (+32° to +122° F)

Storage Temperature -25° to +70° C (13° to +158° F)

Operating Humidity 5% to 95% (non-condensing),
0 – 10000 ft. altitude

REGULATORY APPROVALS

FCC Class A, UL/CUL, CE, CSA

MECHANICAL DIAGRAM

units - inches

