



Band Size	Circumference	
	Min.	Max.
Small	5.5" (140mm)	9" (229mm)
Medium	6" (152mm)	11" (279mm)
Large	7" (178mm)	12" (305mm)

Item	Band Size	Coil Cord
19886	Small	Not Included
19887	Medium	Not Included
19888	Large	Not Included
19900	Small	6' (19906)
19901	Medium	6' (19906)
19902	Large	6' (19906)
19903	Small	12' (19907)
19904	Medium	12' (19907)
19905	Large	12' (19907)

- A. .002" polyphenylsulfone sheet laminated to each link. Provides >5,000 Volt RMS insulation per ASTM D149. Will not flake or peel.
- B. Unique dual contact design is to be paired with a [Desco MagSnap™ 360 Coil Cord](#) (not included) for a superior electrical connection. The magnetic connection made with the coil cord maintains a 1-5 pound perpendicular breakaway force to prevent accidental disconnects.
- C. Black ABS plastic cap. Molded with "MagSnap 360" trademark.
- D. Underwriters Laboratory Listing 90P1C.
- E. Inside links are constructed of 300 Series Stainless Steel. Width of links is 0.63".
- F. Black ABS plastic insulator separates band into halves.

Meets required limits of ANSI/ESD S20.20 and requirements of ANSI/ESD S1.1.

All tolerances are 10% unless otherwise specified. Specifications and procedures are subject to change without notice.

U.S. Patent Pending



MAGSNAP 360™ DUAL-WIRE METAL EXPANSION WRISTBAND

DESCO WEST: 3651 WALNUT AVE, CHINO, CA 91710 WEBSITE: [Desco.com](#)
PHONE: (909) 627-8178

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407
PHONE: (781) 821-8370

**DRAWING
NUMBER**
19886

DATE
February
2019

DESCO