



## Main

|                               |  |
|-------------------------------|--|
| Range of Product              | Telemecanique Photoelectric sensors XU |
| Series name                   | General purpose single mode            |
| Electronic sensor type        | Photo-electric sensor                  |
| Sensor name                   | XUB                                    |
| Sensor design                 | Cylindrical M18                        |
| Detection system              | Diffuse                                |
| Material                      | Metal                                  |
| Line of sight type            | Axial                                  |
| Type of output signal         | Discrete                               |
| Supply circuit type           | DC                                     |
| Wiring Technique              | 3-wire                                 |
| Discrete output type          | PNP                                    |
| Discrete output function      | 1 NO                                   |
| Electrical connection         | Cable                                  |
| Cable length                  | 6.56 ft (2 m)                          |
| Product Specific Application  | -                                      |
| Emission                      | Infrared diffuse                       |
| [Sn] nominal sensing distance | 0.33 ft (0.1 m) diffuse                |

## Complementary

|                           |  |
|---------------------------|--|
| Enclosure Material        | Nickel Plated Brass                              |
| Lens material             | PMMA   |
| Maximum sensing distance  | 0.49 ft (0.15 m) diffuse                         |
| Output Type               | Solid state                                      |
| Add on output             | Without  |
| Wire insulation material  | PvR  |
| Status LED                | 1 LED yellow)output state                        |
| [Us] rated supply voltage | 12...24 V DC reverse polarity protection         |
| Supply voltage limits     | 10...36 V DC                                     |
| Switching capacity in mA  | <= 100 mA overload and short-circuit protection) |
| Switching frequency       | <= 500 Hz  |
| Maximum voltage drop      | <1.5 V closed state)                             |
| Current consumption       | 35 mA no-load                                    |
| Maximum delay first up    | 15 ms  |
| Maximum delay response    | 1 ms   |
| Maximum delay recovery    | 1 ms   |
| Setting-up                | Without sensitivity adjustment                   |
| Diameter                  | 0.71 in (18 mm)                                  |
| Length                    | 2.36 in (60 mm)                                  |
| Net Weight                | 0.11 lb(US) (0.05 kg)                            |

## Environment

|                                       |  |
|---------------------------------------|--|
| Product Certifications                | UL<br>CSA<br>CE  |
| Ambient air temperature for operation | -13...131 °F (-25...55 °C)   |
| Ambient Air Temperature for Storage   | -40...158 °F (-40...70 °C)   |
| Vibration resistance                  | 7 gn +/- 1.5 mm 10...55 Hz IEC 60068-2-6                             |
| Shock resistance                      | 30 gn 11 ms) IEC 60068-2-27  |
| IP degree of protection               | IP67 double insulation IEC 60529<br>IP65 double insulation IEC 60529 |






## Ordering and shipping details

|                       |                                     |
|-----------------------|-------------------------------------|
| Category              | 22415-SENSORS, PHOTOELECTRIC, BASIC |
| Discount Schedule     | DS2                                 |
| GTIN                  | 3389110155495                       |
| Nbr. of units in pkg. | 1                                   |
| Package weight(Lbs)   | 3.88 oz (110.0 g)                   |
| Returnability         | No                                  |
| Country of origin     | ID                                  |

## Packing Units

|                              |                        |
|------------------------------|------------------------|
| Unit Type of Package 1       | PCE                    |
| Package 1 Height             | 1.65 in (4.2 cm)       |
| Package 1 width              | 3.78 in (9.6 cm)       |
| Package 1 Length             | 5.20 in (13.2 cm)      |
| Unit Type of Package 2       | S02                    |
| Number of Units in Package 2 | 22                     |
| Package 2 Weight             | 6.29 lb(US) (2.853 kg) |
| Package 2 Height             | 5.91 in (15 cm)        |
| Package 2 width              | 11.81 in (30 cm)       |
| Package 2 Length             | 15.75 in (40 cm)       |


## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           |  <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)  <a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes   |
| RoHS exemption information |  <a href="#">Yes</a>   |
| Environmental Disclosure   |  <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        |  <a href="#">End Of Life Information</a>   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

## Dimensions




---

## Wiring Schemes


---

### PNP Outputs



BN : Brown  
BU : Blue  
BK : Black

## Detection Curves



- 1 : White 90%
  - 2 : Grey 18%
- Object 10 x 10 cm